30000

DISTRIBUTION HEALTHCARE SOLUTIONS Medical Equipment





Medical equipment and devices must meet industry standards, maintaining performance and functionality despite frequent and rigorous disinfection with harsh chemicals and cleaners, exposure to ultraviolet rays and impact during use. As a medical equipment and device manufacturer, your highperformance, ergonomically designed equipment requires robust materials with high resistance to chemicals, UV rays and impact.

At Avient Distribution, we help you solve your toughest application challenges by providing a specialized approach to the latest material, colorant and additive technologies. With a dedication to sustainable solutions, technical and logistics expertise and innovative design engineering capabilities, we can help you mitigate risk, optimize design, and accelerate product commercialization.

Challenge Accepted.

RIGID COMPONENTS: DIAGNOSTIC, IMAGING, LIFE SUPPORT, LABORATORY, & MONITORING EQUIPMENT

| Applications incl • Housings • Covers • Monitor beze • Body panels • Handles | Access panels Battery enclosures Wands | Rigid Component Solution Needs: Materials compliant with ISO 10993 & USP Class VI, if required UL approved resins to meet flammability requirements Housings with toughness & good impact resistance Enclosures & components that withstand repeated cleanings High-flow materials for components with complex designs |
|--|--|---|
| Copolyester, Po | lyester & PC/Polyester Blend | ds |
| Copolyester | Eastman Tritan [™] (Copolyester) | High chemical resistance to a wide variety of hospital disinfectants; excellent toughness and impact resistance after disinfection; retains color and gloss after sterilization and disinfection; does not contain BPA, BPS or halogens |
| Polybutylene Terephthalate (PBT) | DuPont [™] Crastin® & Rynite® (FR-PBT) | 30% glass reinforced; flame retardant; good mold flow and electrical properties; high strength, stiffness, dimensional stability and heat resistance |
| Polycarbonate/ Polyester (PC/PET) & Polycarbonate/ Polybutylene Terephthalate (PC/PBT) | Covestro Makroblend [®] (FR-PC/PET) & (FR-PC/PBT) | Strength; toughness; chemical resistance; flame retardant |
| | Covestro Makroblend® (Non-FR PC/PBT) | Strength; toughness; chemical resistance; limited biocompatibility |
| | Trinseo EMERGE [™] (FR-PC/PET) | Chemical resistance; ignition resistance; limited biocompatibility |
| PA, PVC, PC & P | мма | |
| Polyamide | Avient Trilliant [™] XR Radiation Shielding (PA) | Radiation shielding; green alternative for lead replacement; enhanced design freedom vs. lead; available in hard and soft durometers |
| (Nylon, PA) | Arkema Rilsan [®] MED (PA11) & Rilsamid [®] MED (PA12) | Chemical resistance; transparent and opaque; easy processing; creep resistance; temperature resistance; BPA-free; sterilizable by gamma, EtO and steam |
| Polyvinyl Chloride (PVC) | GEON Performance Solutions Resilience [™] HC (PVC) | Excellent chemical resistance; good strength and stiffness; very good surface quality; inherently flame resistant; available in all medical colors; excellent solvent bonding to PVC |
| Polycarbonate (PC) | Trinseo EMERGE [™] (PC) | Ignition resistant; transparent and opaque; glass-filled also available |
| PolyMethyl Methacrylate (PMMA) | Trinseo Plexiglas® Acrylics (PMMA) | Clarity; easy processing; chemical resistance; BPA free; ideal for light piping and lenses |
| Styrenics & FR- | PC/ABS Blends | |
| Styrenics | Trinseo MAGNUM [™] (ABS) | Opaque; custom colors; excellent impact and flow; low residuals; full biocompatibility |
| | INEOS Styrolution Terlux® HD (MABS) | Good clarity; good heat and overall chemical resistance; good impact strength; good solvent bonding to PVC; outstanding surface quality |
| | INEOS Styrolution Lustran® & Novodur® HD (ABS) | Opaque appearance; outstanding chemical resistance; high impact strength; excellent balance of properties; ease of processability; bondable |
| FR- Polycarbonate/ ABS (FR-PC/ABS) | Covestro Bayblend® (FR-PC/ABS) | Flame retardant; good impact resistance; dimensional stability; toughness |
| | Trinseo EMERGE [™] (FR-PC/ABS) | Ignition resistant; limited biocompatibility; high flow; easy processing; glass-filled also available |

FLEXIBLE COMPONENTS: DIAGNOSTIC, IMAGING, LIFE SUPPORT, LABORATORY, & MONITORING EQUIPMENT

| Applications incl • O-rings • Gaskets • Wheels • Soft touch grips/handle | Keypads/displaysDiaphragmsSeals | Flexible Component Solution Needs: • Comfortable handles & grips • Water-tight seals • Durable feet or casters • Durable keypads • Flow control |
|---|---|--|
| ТРЕ, ТРС-ЕТ, ТР | PU, TPV & Flexible PVC | |
| Thermoplastic Elastomers (TPE) | Avient Versaflex [™] HC Overmolding Series (TPE) | Proven healthcare solutions with hardness ranges 42–65 Shore A; autoclave, radiation and EtO sterilizable; bondable to many substrates; customizable haptics |
| | Arkema Pebax [®] MED (TPE) | Sterilizable by gamma and EtO; low energy return; soft touch; chemical resistance; overmolding material |
| Thermoplastic Polyester Elastomers (TPC-ET) | DuPont [™] Hytrel® (TPC-ET) | Wide range of flexibility, stiffness, and processing options; Shore D between 30-82; BPA-free; excellent flex fatigue and toughness; low temperature flexibility; good chemical resistance |
| Thermoplastic Polyurethane (TPU) | Covestro Texin [®] (TPU) | Biocompatible; soft touch; sterilizable; good chemical resistance; overmold for grips and handles; excellent bonding to polar substrates like PC; 70A to 95A |
| Thermoplastic Vulcanizate (TPV) | Avient Versalloy [™] (TPV) | Proven healthcare solutions with hardness ranges 45–90 Shore A; autoclave, radiation and EtO sterilizable; natural and colorable; smooth texture; bonds to PP |
| | Exxon Mobil Santoprene [™] (TPV) | Durable sealing performance; elastic recovery; excellent chemical resistance; compliance with medical standards |
| Flexible Polyvinyl Chloride (PVC) | GEON Performance Solutions Geon [™] Flexible PVC | Engineered exclusively for the healthcare market; transparent and opaque colors; radiopaqu grades available; durometer ranges from 55A to 40D; gamma and EtO sterilizable |
| Thermoset Silio | cone Elastomers | |
| Thermoset Silicone | DuPont™Liveo™ | Biocompatible: non-irritating and non-sensitization: sterilizable: |



WIRE & CABLE: DIAGNOSTIC, IMAGING, LIFE SUPPORT, LABORATORY, & MONITORING EQUIPMENT

| Applications include: Plug molding Flexible cords Flexible jacket Coil cords & cable Heater cable insulation | | Wire & Cable Component Solution Needs: Materials compliant with UL, RoHS, REACH & WEEE, if needed Materials with good chemical, moisture & abrasion resistance Low smoke & non-halogen materials |
|---|--|---|
| PVC | | |
| Polyvinyl Chloride (PVC) | GEON Performance Solutions Geon [™] Flexible PVC | Inherent flame resistance; halogen-free; excellent chemical resistance; non-yellowing; proven safety record in wire and cable applications; high temperature grades available |
| TPE, TPC-ET, TP | U & POE | |
| Thermoplastic Polyester (TPE) | Arkema Pebax [®] (TPE) | Flexibility; chemical resistance; easy processing; abrasion resistance; low coefficient of friction |
| Thermoplastic Polyester Elastomers (TPC-ET) | DuPont [™] Hytrel® (TPC-ET) | REACH, RoHS and WEEE compliant; wide range of flexibility, stiffness, and processing options; 30D-82D; BPA-free; excellent flex fatigue and toughness; low temperature flexibility; good chemical resistance |
| Thermoplastic Polyurethane (TPU) | Covestro Texin [®] (TPU) | RoHs, WEEE, and REACH compliant; excellent memory and recoil; abrasion resistance; Texin® Rx Series - medical grade Polyether TPU – 70A to 80D |
| Polyolefin Elastomer (POE) | Avient ECCOH [™] | Non-halogenated flame retardant; high flexibility; environmental stress cracking resistance (ESCR); good electrical properties |
| PA | | |
| Polyamide (Nylon, PA) | Arkema Rilsan [°] (PA) | Chemical resistance; easy processing; abrasion resistance; low coefficient of friction; dimensional stability |



CUSTOM AVIENT SOLUTIONS FOR MEDICAL EQUIPMENT

| Custom Solution Needs | Avient [™] Custom Solutions |
|--|--|
| Specialized materials to meet unique application requirements | Avient Trilliant [™] Healthcare products are a line of customized solutions specific for regulated medical devices; color branding expertise |
| FDA-registered pre-colored resins and masterbatch options; color coding for safety and brand recognition | Avient collaborates with key material suppliers to provide FDA-approved pre-colored resins Avient OnColor [™] HC Plus offers customizable color masterbatch solutions pre-certified for biocompatibility using ISO 10993 and USP Class VI test protocol |
| Reduced growth of microbes | Avient WithStand [™] additive technologies inhibit growth of microbes that often cause odor, staining and loss of mechanical properties |



AVIENT DISTRIBUTION Healthcare Supplier Line Card

You face a unique set of challenges when designing parts for the healthcare industry. In addition to maintaining an effective manufacturing and supply chain operation, you're challenged with designing products that must meet strict regulatory and quality assurance standards. At Avient Distribution, we help you achieve these goals with our comprehensive portfolio of leading suppliers, on-time delivery and a host of services focused on helping you succeed.



AVIENT DISTRIBUTION HEALTHCARE SOLUTIONS

At Avient Distribution, we're prepared to help you:

- Mitigate risk
- Optimize design
- Accelerate commercialization

Contact us today to learn more about how we can help you overcome your toughest challenges.



MEDICAL EQUIPMENT THAT'S EQUIPPED TO PERFORM

Your medical equipment needs to be durable and properly perform every time. With the right polymers, your equipment will not only resist cracking, but can also bring greater comfort to both the patient and the physician.

- Housings
- Covers
- Panels
- Enclosures
- Handles
- Wands
- Coils
- O-rings

- Gaskets
- Wheels
- Soft-Touch Components
- Keypad Displays

1.844.4AVIENT www.avientdistribution.com



Copyright © 2021, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.