

# Trilliant™ HC Glass-Filled Polyketone Grades

STANDARD COLORS FOR  
BIOPHARMACEUTICAL  
APPLICATIONS

Formulated to provide outstanding chemical resistance, the Trilliant™ HC Glass-Filled (GF) polyketone (PK) portfolio includes grades with 10–33% GF levels to meet various performance demands. These grades are available in many standard colors and all are ISO 10993 compliant. These advanced healthcare grades also allow for additional customization to meet specific color or application requirements.

## TRILLIANT HEALTHCARE GF PK FORMULATIONS

| GLASS FILL | COLOR           | PRODUCT NAME   |
|------------|-----------------|----------------|
| 10%        | Bright White    | HC8910-0004 RS |
| 20%        |                 | HC8910-0017 RS |
| 33%        |                 | HC8910-0018 RS |
| 10%        | Cool Gray 1C    | HC8910-0005 RS |
| 20%        |                 | HC8910-0006 RS |
| 10%        | Cool Gray 3C    | HC8910-0007 RS |
| 20%        |                 | HC8910-0008 RS |
| 10%        | Warm Gray 1 C   | HC8910-0009 RS |
| 20%        |                 | HC8910-0010 RS |
| 10%        | TPX 12-0703 Tan | HC8910-0011 RS |
| 20%        |                 | HC8910-0012 RS |
| 10%        | 542C Blue       | HC8910-0013 RS |
| 20%        |                 | HC8910-0014 RS |
| 10%        | 301C Blue       | HC8910-0015 RS |
| 20%        |                 | HC8910-0016 RS |

Colors may vary from actual color shown

1.844.4AVIENT  
www.avient.com



Copyright © 2021, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as “typical” or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient’s products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.