10051945 YELLOW DS

Version Number 1.8 Revision Date 04/16/2024



Page 1 of 17 Print Date 04/17/2024

SAFETY DATA SHEET

10051945 YELLOW DS

Section 1. Identification		
GHS product identifier Chemical name CAS number Other means of identification Product type	:	10051945 YELLOW DS Mixture Mixture CC00003705 solid
	: ance	or mixture and uses advised against
Product use	:	Industrial applications. Plastics.
Supplier's details	:	AVIENT CORPORATION 33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (844) 4AVIENT
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	COMBUSTIBLE DUSTS
GHS label elements		
Signal word Hazard statements	:	Warning May form combustible dust concentrations in air.

|--|

ÀVIENT

10051945 YELLOW DS

Version Number 1.8 Revision Date 04/16/2024 Page 2 of 17 Print Date 04/17/2024

	:	Not applicable.
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	Keep container tightly closed.
Hazards not otherwise classified	:	None known.
		Not available.

Section 3. Composition/information on ingredients

:

:

:

Substance/mixture Chemical name Other means of identification Mixture Mixture CC00003705

CAS number/other identifiers

Ingredient name	%	CAS number
Titanium dioxide	>= 50 - <= 75	13463-67-7
Silica, amorphous	>= 3 - <= 5	7631-86-9

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated

10051945 YELLOW DS

Version Number 1.8 Revision Date 04/16/2024

ÀVIENT

Page 3 of 17

Print Date 04/17/2024

Ingestion	:	clothing and shoes. Get medical attention if symptoms occur. Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.	
Most important symptoms/effect	as, acute a	nd delayed	
Potential acute health effects			
Eye contact	:	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the eyes.	
Inhalation	:	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.	
Skin contact	:	No known significant effects or critical hazards.	
Ingestion	:	No known significant effects or critical hazards.	
Over-exposure signs/symptoms			
Eye contact	:	Adverse symptoms may include the following: irritation	
Inhalation	:	redness Adverse symptoms may include the following: respiratory tract irritation coughing	
Skin contact	:	No specific data.	
Ingestion	:	No specific data.	
Indication of immediate medical attention and special treatment needed, if necessary			
Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under	
Specific treatments	:	medical surveillance for 48 hours. No specific treatment.	
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training.	

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Unsuitable extinguishing media : Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.	Suitable extinguishing media Unsuitable extinguishing media	:	
---	--	---	--

10051945 YELLOW DS

Version Number 1.8 Revision Date 04/16/2024



Page 4 of 17 Print Date 04/17/2024

Specific hazards arising from the chemical	:	May form explosible dust-air mixture if dispersed.
Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides halogenated compounds metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire- exposed containers cool.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing dust. Put on appropriate	
For emergency responders	:	personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	
Methods and materials for containment and cleaning up			
Small spill	:	Move containers from spill area. Use spark-proof tools and explosion- proof equipment. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.	
Large spill	:	Move containers from spill area. Use spark-proof tools and explosion- proof equipment. Approach release from upwind. Prevent entry into	
		4/17	

10051945 YELLOW DS

Version Number 1.8 Revision Date 04/16/2024



Page 5 of 17 Print Date 04/17/2024

sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing dust. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

10051945 YELLOW DS

Version Number 1.8 Revision Date 04/16/2024



Page 6 of 17 Print Date 04/17/2024

Occupational exposure limits

Ingredient name	Exposure limits
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (2022-01-06) TWA 0.2 mg/m3 Form: respirable fraction, nanoscale particles TWA 2.5 mg/m3 Form: respirable fraction, finescale particles
Silica, amorphous	NIOSH REL (1994-06-01) TWA 6 mg/m3

Appropriate engineering controls Environmental exposure controls	:	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. If operating conditions cause high dust concentrations to be produced, use dust goggles.

10051945 YELLOW DS

Versio Revis

ÀVIENT

ion Number 1.8	Page 7 of 17
sion Date 04/16/2024	Print Date 04/17/2024

Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state	:	solid [Very fine powder.]
•		
Color	:	YELLOW
Odor	:	Not available.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not applicable.
Burning time		Not available.
Burning time	:	r (of a (anabie)
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not applicable.
(flammable) limits		Upper: Not applicable.
Vapor pressure	:	Not available.
Vapor density	:	Not applicable.

10051945 YELLOW DS

Version Number 1.8 Revision Date 04/16/2024

ÀVIENT

Page 8 of 17 Print Date 04/17/2024

Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n-	:	Not applicable.
octanol/water		
Auto-ignition temperature	:	Not applicable.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	Dynamic: Not available.
-		Kinematic: Not applicable.

Aerosol product

Heat of combustion	:	Not available.
Ignition distance	:	Not available.
Enclosed space ignition - Time equivalent	:	Not available.
Enclosed space ignition -	:	Not available.
Deflagration density		
Flame height	:	Not available.
Flame duration	:	Not available.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation.
Incompatible materials	:	Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced. Prolonged heating may result in product degradation. As a general

10051945 YELLOW DS

Version Number 1.8 Revision Date 04/16/2024

ÀVIENT

Page 9 of 17 Print Date 04/17/2024

rule of thumb, degradation begins to occur after one hour at 177 °C (350 °F), after 10 minutes at 204 °C (400 °F), and within 5 minutes at 232 °C (450 °F). Do not use this pigment in polymers at temperatures over 200°C (392°F). Decomposition of diarylide pigments in polymers at temperatures over 200°C (392°F) may produce trace amounts of monoazo dyes, which in turn can decompose to produce aromatic amines. The amount and type of degradation products formed depend on the dwell time, formulation and processing conditions as well as temperature. As conditions become more severe, as when temperatures move into the 240-300°C (464-572°F) range, trace quantities of 3,3'-dichlorobenzidine can be generated. 3,3'dichlorobenzidine is classified as a suspect carcinogen by NTP and IARC, is classified as Acute Toxicity category 4 and Carcinogen Category 1B according to 1272/2008EC (CLP), and is regulated by OSHA as a suspect carcinogen. In order to avoid the generation of and exposure to 3,3'-dichlorobenzidine, do not use diarylide pigments in polymers when temperatures exceed 200°C (392°F). Handle with care. Organic dusts have the potential to be explosive with static spark or flame initiation.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Titanium oxide (TiO2)				
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h
	Dusts and mists			
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-

Conclusion/Summary

: Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Silica	Eyes - Mild irritant	Rabbit	-	24 hrs	-

Conclusion/Summary
Skin
Eyes

Mixture.Not fully tested. Mixture.Not fully tested. Mixture.Not fully tested.

:

:

•

Sensitization

Respiratory

Conclusion/Summary

10051945 YELLOW DS

Version Number 1.8 Revision Date 04/16/2024



Page 10 of 17
Print Date 04/17/2024

Skin Respiratory	Mixture.Not fully tested.Mixture.Not fully tested.				
Mutagenicity					
Conclusion/Summary	: M	ixture.Not fully t	ested.		
Carcinogenicity					
Conclusion/Summary	: M	ixture.Not fully t	ested.		
<u>Classification</u>					
Product/ingredient name	OSHA	IARC	NTP		
Titanium oxide (TiO2)	-	2B	-		
Silica	-	3	-		
<u>Reproductive toxicity</u> Conclusion/Summary <u>Teratogenicity</u>	: M	ixture.Not fully t	ested.		
Conclusion/Summary	: M	ixture.Not fully t	ested.		
<u>Specific target organ toxicity (single exposure)</u> Not available.					
<u>Specific target organ toxicity (repeated exposure)</u> Not available.					
Aspiration hazard Not available.					
Information on the likely routes of : Not available. exposure					
Potential acute health effects					

Eye contact	: Exposure to airborne concentrations above statutory or recommended
	exposure limits may cause irritation of the eyes.
Inhalation	: Exposure to airborne concentrations above statutory or recommended
	exposure limits may cause irritation of the nose, throat and lungs.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

10051945 YELLOW DS

Version Number 1.8 Revision Date 04/16/2024



Page 11 of 17
Print Date 04/17/2024

Eye contact Inhalation Skin contact Ingestion Delayed and immediate effects and a	: : : lso c	Adverse symptoms may include the following: irritation, redness Adverse symptoms may include the following: respiratory tract irritation, coughing No specific data. No specific data. hronic effects from short and long term exposure
<u>Short term exposure</u> Potential immediate effects	:	Not available.
Potential delayed effects <u>Long term exposure</u>	:	Not available.
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.
General Carcinogenicity Mutagenicity Teratogenicity Developmental effects Fertility effects	::	Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. No known significant effects or critical hazards. No known significant effects or critical hazards.
<u>Numerical measures of toxicity</u> <u>Acute toxicity estimates</u> N/A		effects or critical hazards.
Other information	:	This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Section 12. Ecological information

10051945 YELLOW DS

Version Number 1.8 Revision Date 04/16/2024

ÀVIENT

Page 12 of 17
Print Date 04/17/2024

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium oxide (TiO2)	·		
	Acute LC50 > 1,000 Mg/l	Fish - Fundulus heteroclitus	96 h
	Marine water		
	Acute LC50 3 Mg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 h
	Acute LC50 6.5 Mg/l Fresh	Daphnia - Daphnia pulex	48 h
	water	Dupinina Dupinina pulox	10 11
Conclusion/Summary	: Not available.		
Persistence and degradability			
Conclusion/Summary	: Not available.		
<u>Bioaccumulative potential</u> Not available. Mobility in soil			
Soil/water partition coefficie (KOC)	ent : Not available.		
Other adverse effects	: No known significant	t effects or critical hazards.	
Section 13. Dispose	al considerations		
Disposal methods	possible. Disposal of should at all times co protection and waste authority requiremen products via a license disposed of untreated requirements of all au	ste should be avoided or minimize this product, solutions and any by mply with the requirements of env disposal legislation and any region ts. Dispose of surplus and non-rec ed waste disposal contractor. Waste to the sewer unless fully complian athorities with jurisdiction. Waste ncineration or landfill should only	-products vironmental hal local yclable e should not be nt with the packaging

when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling

10051945 YELLOW DS

Version Number 1.8 Revision Date 04/16/2024



Page 13 of 17 Print Date 04/17/2024

and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	:	Not regulated for transportation.
International Air ICAO/IATA	:	Consult mode specific transport rules
International Water IMO/IMDG	:	Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations	:	United States - TSCA 12(b) - Chemical export notification: None
-		of the components are listed.
		United States - TSCA 4(a) - Final Test Rules: Not listed
		United States - TSCA 4(a) - ITC Priority list: Not listed
		United States - TSCA 4(a) - Proposed test rules: Not listed
		United States - TSCA 4(f) - Priority risk review: Not listed
		United States - TSCA 5(a)2 - Final significant new use rules: Not
		listed
		United States - TSCA 5(a)2 - Proposed significant new use rules:
		Not listed
		United States - TSCA 5(e) - Substances consent order: Not listed
		United States - TSCA 6 - Proposed risk management: Not listed
		United States - TSCA 8(a) - Chemical risk rules: Not listed
		United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed
		United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not
		determined
		United States - TSCA 8(a) - Preliminary assessment report
		(PAIR): Not listed
		United States - TSCA 8(c) - Significant adverse reaction (SAR):
		Not listed
		United States - TSCA 8(d) - Health and safety studies: Not listed
		United States - TSCA 6 - Final risk management: Not listed
		United States - EPA Clean water act (CWA) section 307 - Priority
		pollutants: Listed Zinc stearate
		Zinc ferrite brown spinel (C.I. Pigment Yellow 119)
		13/17

10051945 YELLOW DS

Version Number 1.8 Revision Date 04/16/2024

ÀVIENT

Page 14 of 17 Print Date 04/17/2024

United States - EPA Clean water act (CWA) section 311 -Hazardous substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	:	Not listed
Clean Air Act Section 602 Class I	:	Not listed
Substances Clean Air Act Section 602 Class II	:	Not listed
Substances DEA List I Chemicals (Precursor	:	Not listed
Chemicals)		Not listed
DEA List II Chemicals (Essential Chemicals)	:	Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

:

not applicable

SARA 311/312

Classification

COMBUSTIBLE DUSTS

Composition/information on ingredients

Name	%	Classification
Titanium oxide (TiO2)	>= 50 - <= 75	CARCINOGENICITY - Category 2
Octadecanoic acid, zinc salt (2:1)	>= 10 - <= 25	COMBUSTIBLE DUSTS
Silica	>= 3 - <= 5	EYE IRRITATION - Category 2B

SARA 313

Form R - Reporting requirements

Product name	CAS number	%
Zinc stearate	557-05-1	>= 10 - < 30

10051945 YELLOW DS

Version Number 1.8 Revision Date 04/16/2024

ÀVIENT

Page 15 of 17 Print Date 04/17/2024

	-	
Aluminum oxide	1344-28-1	>= 1 - < 5
A Hummun Oxide	1344 20 1	$\gamma = 1 < 5$

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations	
Massachusetts	: The following components are listed: Titanium dioxide Zinc stearate Calcium carbonate Silica, amorphous Aluminum oxide
New York	: None of the components are listed.
New Jersey	: The following components are listed: Titanium dioxide Zinc stearate Calcium carbonate Aluminum oxide
Pennsylvania	: The following components are listed: Titanium dioxide
	Zinc stearate
	Calcium carbonate
	Silica, amorphous
	Aluminum oxide

California Prop. 65

WARNING: This product can expose you to Titanium dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Titanium dioxide	-	-

United States inventory (TSCA 8b)	:	All components are active or exempted.
Canada inventory	:	At least one component is not listed in DSL but all such components are listed in NDSL.

10051945 YELLOW DS

Version Number 1.8 Revision Date 04/16/2024



Page 16 of 17 Print Date 04/17/2024

International regulations	
Inventory list	
Australia	: Not determined.
Canada	: At least one component is not listed in DSL but all such components are listed in NDSL.
China	: All components are listed or exempted.
Eurasian Economic Union	: Russian Federation inventory: Not determined.
Japan	: Japan inventory (CSCL): Not determined.
_	Japan inventory (ISHL): Not determined.
New Zealand	: All components are listed or exempted.
Philippines	: Not determined.
Republic of Korea	: All components are listed or exempted.
Taiwan	: Not determined. All components are listed or exempted.
Thailand	: Not determined.
Turkey	: Not determined.
United States	: All components are active or exempted.
Viet Nam	: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	0
Flammability		3
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

<u>Illstol y</u>	
Date of printing	: 04/17/2024
Date of issue/Date of revision	: 04/16/2024
Date of previous issue	: 07/21/2016
Version	: 1.8
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container

10051945 YELLOW DS

Version Number 1.8 Revision Date 04/16/2024

AVIENT

Page 17 of 17 Print Date 04/17/2024

IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations Not available.

References

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.