

MATERIAL SAFETY DATA SHEET

LOGO RED HSP UV-PE

Version Number 1.0 Revision Date 09/20/2001 Page 1 of 6 Print Date 11/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	LOGO RED HSP UV-PE
Product code	:	CC10001651
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-, polymer with 2,4,6-trichloro-1,3,5-triazine, reaction products with2	70624-18-9	5 - 10
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Resin particles, like other inert materials, can be mechanically irritating.
May be harmful if swallowed.
Resin particles, like other inert materials, are mechanically irritating to eyes.
Experience shows no unusual dermatitis hazard from routine handling.



MATERIAL SAFETY DATA SHEET

LOGO RED HSP UV-PE

ision Date 09/20/2001	Print Date 11/1/2
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET

LOGO RED HSP UV-PE

sion Number 1.0 rision Date 09/20/2001			Print	Page 3 (Date 11/1/2)
Handling		ake measures to prevent the b nly in areas with appropriate e		aarge. Heat
Storage		eep containers dry and tightly nd contamination. Keep in a c		e absorption
8. H	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	o personal respiratory protect	ive equipment normally i	required.
Eye/Face Protection	: S	afety glasses with side-shields		
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations		andle in accordance with good Vash hands before breaks and		afety practice.
Engineering measures		leat only in areas with appropr ppropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	9. PHYSIC	CAL AND CHEMICAL PRO	DPERTIES	
Form Appearance Color	: Solic : Pelle : RED	ts Specif Bulk c	ic Gravity : Not lensity : Not	applicable. determined. established
Odor Melting point/range Boiling Point:			density : Not	applicable applicable applicable

10. STABILITY AND REACTIVITY

Stability	:	Stable.
-----------	---	---------

Hazardous Polymerization	:	Will not occur
--------------------------	---	----------------

Conditions to avoid

Will not occur.

: Keep away from oxidizing agents and open flame. To avoid thermal



MATERIAL SAFETY DATA SHEET

LOGO RED HSP UV-PE

	2001		Pr	rint Date 11/1/2
	decomposition	, do not overheat.		
Incompatible Mater	ials : Incompatible v	with strong acids a	nd oxidizing agents	
Hazardous decompo products			onoxide (CO), oxid s, and smoke are all	
	11. TOXICOLOGI	CAL INFORMA	TION	
health data for the i	t been evaluated as a whole for l ndividual components which con			are based on exi
<u>Toxicity Overview</u> This product contai	ns the following components wh	ich in their pure fo	orm have the follow	ing characteristic
CAS-No.	Chemical Name	Effect	Targ	get Organ
70624-18-9	1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products with2	Highly Toxic	Refer to MSE Data	DS for Toxicity
13463-67-7	Titanium dioxide	Systemic effect	Respiratory s	ystem.
LC50 / LD50 This product contai	ns the following components wh	ich in their pure fo	orm have the follow	ing toxicity data
	Chemical Name 1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi	ich in their pure fo Route LC50 Oral LD50	orm have the follow Value 112 mgm34H 9,910 mg/kg	ing toxicity data Species rat rat
This product contai	Chemical Name 1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with	Route LC50	Value 112 mgm34H	Species rat
This product contai	Chemical Name 1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi	Route LC50 Oral LD50	Value 112 mgm34H 9,910 mg/kg	Species rat
This product contai	Chemical Name 1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products with2 12. ECOLOGIC	Route LC50 Oral LD50	Value 112 mgm34H 9,910 mg/kg	Species rat
This product contai CAS-No. 70624-18-9	Chemical Name 1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products with2 12. ECOLOGICA radability : Not readily bio	Route LC50 Oral LD50	Value 112 mgm34H 9,910 mg/kg	Species rat rat
This product contai CAS-No. 70624-18-9 Persistence and deg	Chemical Name 1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products with2 12. ECOLOGIC radability : Not readily bio icity : Chemicals are of the polymer	Route LC50 Oral LD50 AL INFORMATI degradable. not readily availab	Value 112 mgm34H 9,910 mg/kg	Species rat rat
This product contai CAS-No. 70624-18-9 Persistence and deg Environmental Tox	Chemical Name 1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products with2 12. ECOLOGIC radability : Not readily bio icity : Chemicals are of the polymer of the polymer	Route LC50 Oral LD50 AL INFORMATI degradable. not readily available.	Value 112 mgm34H 9,910 mg/kg ION	Species rat rat
This product contai <u>CAS-No.</u> 70624-18-9 Persistence and deg Environmental Tox Bioaccumulation Pe	Chemical Name 1,6-Hexanediamine, N,N'-bis(2,2,6,6-tetrameth yl-4-piperidinyl)-,polymer with 2,4,6-trichloro-1,3,5-triazi ne, reaction products with2 12. ECOLOGIC radability : Not readily bio icity : Chemicals are of the polymer of the polymer	Route LC50 Oral LD50 AL INFORMATI degradable. not readily availab . ble.	Value 112 mgm34H 9,910 mg/kg ION Iole as they are bound ole as they are bound	Species rat rat

4/6



MATERIAL SAFETY DATA SHEET

LOGO RED HSP UV-PE

sion Number 1.0 rision Date 09/20/2001		Page 5 0 Print Date 11/1/20
		recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	:	Not regulated for transportation.
ICAO/IATA	:	Not regulated for transportation.
IMO / IMDG	:	Not regulated for transportation.
	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:		
WHMIS Classification	:	D1A
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not Listed.
Japan ENCS	:	Not Listed.
Korea KECI	:	Not Listed.



MATERIAL SAFETY DATA SHEET

LOGO RED HSP UV-PE

Version Number 1.0 Revision Date 09/20/2001 Page 6 of 6 Print Date 11/1/2011

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.