

MATERIAL SAFETY DATA SHEET

YELLOW 106

Version Number 1.0 Revision Date 09/26/2001 Page 1 of 5 Print Date 11/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	YELLOW 106
Product code	:	CC10001689
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some fumes may be released upon heating or crosslinking and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect his employee from exposure. See Sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. 		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure Medical Conditions Aggravated by Exposure:	Refer to Section 11 for Toxicological Information.None known.		



MATERIAL SAFETY DATA SHEET

YELLOW 106

sion Number 1.0 ision Date 09/26/2001	Page 2 Print Date 11/1/2
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
-	
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit Autoignition temperature	: Not applicable : Not relevant
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foam.
Special Fire Fighting	: Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures	pressure mode should be worn to prevent inhalation of airborne
	contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET

YELLOW 106

URE CO : No p : Safet : Prote : Long : Safet : Hanc Wash : Heat appro	ty glasses with si ective gloves. g sleeved clothing ty shoes. dle in accordance h hands before be only in areas wi opriate exhaust v Exposure tin Time Weighted A (TWA):	RSONAL P pry protective ide-shields. g. e with good in reaks and at th appropriat yentilation at me Average	ROTECTION e equipment normally r ndustrial hygiene and s the end of workday. te exhaust ventilation.	safety practic
 No p Safet Prote Long Long Safet Hand Wash Heat approx 	ersonal respirato ty glasses with si ective gloves. g sleeved clothing ty shoes. dle in accordance h hands before bu only in areas wi opriate exhaust v <u>Exposure tin</u> Time Weighted A (TWA):	ory protective ide-shields. g. e with good in reaks and at th appropriat rentilation at me Average	e equipment normally n ndustrial hygiene and s the end of workday. te exhaust ventilation. machinery. Exposure type	afety practic Provide
: Safet : Prote : Long : Safet : Hanc Wash : Heat appro	ty glasses with si ective gloves. g sleeved clothing ty shoes. dle in accordance h hands before be only in areas wi opriate exhaust v Exposure tin Time Weighted A (TWA):	g. e with good in reaks and at th appropriat rentilation at <u>me</u> Average	ndustrial hygiene and s the end of workday. te exhaust ventilation. machinery. Exposure type	afety practic Provide
: Prote : Long : Safet : Hand Wash : Heat appro	ective gloves. g sleeved clothing ty shoes. dle in accordance h hands before b conly in areas wi opriate exhaust v Exposure tin Time Weighted A (TWA):	g. e with good in reaks and at th appropriat ventilation at me Average	the end of workday. te exhaust ventilation. machinery. Exposure type	Provide List:
: Long : Safet : Hanc Wasl : Heat appro	g sleeved clothing ty shoes. dle in accordance h hands before be only in areas wi opriate exhaust v Exposure tin Time Weighted A (TWA):	e with good in reaks and at th appropriat rentilation at me Average	the end of workday. te exhaust ventilation. machinery. Exposure type	Provide List:
: Safet : Hanc Wash : Heat appro	ty shoes. dle in accordance h hands before be only in areas wi opriate exhaust v <u>Exposure tin</u> Time Weighted <i>A</i> (TWA):	e with good in reaks and at th appropriat rentilation at me Average	the end of workday. te exhaust ventilation. machinery. Exposure type	Provide List:
: Hanc Wash : Heat appro	dle in accordance h hands before b only in areas wi opriate exhaust v Exposure tin Time Weighted A (TWA):	reaks and at the appropriate ventilation at the me Average	the end of workday. te exhaust ventilation. machinery. Exposure type	Provide List:
Wash : Heat appro	h hands before be only in areas wi opriate exhaust v Exposure tin Time Weighted A (TWA):	reaks and at the appropriate ventilation at the me Average	the end of workday. te exhaust ventilation. machinery. Exposure type	Provide List:
appro	Exposure tin Time Weighted A (TWA):	me Average	machinery. Exposure type	List:
g/m3 7	Time Weighted A (TWA):	Average		
	(TWA):	-	Dust.	ACGIH
g/m3	DET			
	PEL:		Total dust.	OSHA Z
IYSICAI	L AND CHEMI	CAL PROP	PERTIES	
Not app	nt ermined. licable	Evaporat Specific Bulk der Vapor pi Vapor de pH	Gravity : Not nsity : Not ressure : Not ensity : Not	applicable. determined. established applicable applicable applicable
10. STA	BILITY AND	REACTIVI	ГҮ	
: Stabl	le.			
: Will	not occur.			
			and open flame. To a	avoid therma
: Incor	mpatible with str	ong acids an	d oxidizing agents.	
	Not app Insolubl 10. STA : Stab : Will : Keep deco	 Stable. Will not occur. Keep away from oxid decomposition, do not 	Not applicable pH Insoluble pH 10. STABILITY AND REACTIVE : Stable. : Will not occur. : Keep away from oxidizing agents decomposition, do not overheat.	Not applicable pH : Not Insoluble : Not 10. STABILITY AND REACTIVITY : Stable. : Will not occur. : Keep away from oxidizing agents and open flame. To a decomposition, do not overheat.



MATERIAL SAFETY DATA SHEET

YELLOW 106

Version Number 1.0 Revision Date 09/26/2001

Page 4 of 5 Print Date 11/1/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ			
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.			
	12. ECOLOGI	CAL INFORMATION	1			
Persistence and degrad	ability : Not readily b	viodegradable.				
Environmental Toxicit	y : Chemicals ar of the polym		is they are bound within the matri			
Bioaccumulation Poter		: Chemicals are not readily available as they are bound within the matrix of the polymer.				
Additional advice	: No data avail	lable.				
	13. DISPOSAL	CONSIDERATIONS	9			
Product Contaminated packagin	recycling is p waste materia transportation state/provinc ng : Recycling is has the respo and disposal	 Like most thermoplastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. 				
	14. TRANSPO	ORT INFORMATION				
U.S. D.O.T. / CA T.D. Classification (Non-bu ground)	e	d for transportation.				
ICAO/IATA	: Not regulated	d for transportation.				
IMO / IMDG	: Not regulated	l for transportation.				
	15 RECHLAT	ORY INFORMATION	NI			

MATERIAL SAFETY DATA SHEET



YELLOW 106		
Version Number 1.0 Revision Date 09/26/2001		Page 5 of 5 Print Date 11/1/2011
US Regulations:		
OSHA Status	:	Classified as hazardous
TSCA Status	:	All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
Canadian Regulations:		
WHMIS Classification	:	D2B
DSL	:	Listed.
National Inventories:		
Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not Listed.
Japan ENCS	:	Not Listed.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.