ne

HAZEL DOOR, ISO-FIX COVER

Version Number 1.0 Revision Date 10/13/2020 Page 1 of 18 Print Date 10/16/2020

SAFETY DATA SHEET

HAZEL DOOR, ISO-FIX COVER

Section 1. Identification	on	
GHS product identifier Chemical name CAS number Other means of identification Product type	:	HAZEL DOOR, ISO-FIX COVER Mixture Mixture CC10330924 liquid
<u>Relevant identified uses of the subs</u> Product use	tance :	e or mixture and uses advised against Industrial applications. Plastics.
Supplier's details	:	POLYONE CORPORATION ColorMatrix Group Inc. 680 North Rocky River Drive, Berea, Ohio, 44017-1628, USA
		+1 216 622 0100
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	SKIN IRRITATION - Category 2 SKIN SENSITIZATION - Category 1

GHS label elements



HAZEL DOOR, ISO-FIX COVER

Version Number 1.0 Revision Date 10/13/2020 Page 2 of 18 Print Date 10/16/2020

Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	Causes skin irritation.
		May cause an allergic skin reaction.
Precautionary statements		
	:	Not applicable.
Prevention	:	Wear protective gloves. Avoid breathing vapor. Wash thoroughly after handling.
Response	:	Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known.
		Not available.

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	CC10330924

CAS number/other identifiers

Ingredient name	%	CAS number
Miscellaneous Compounds Distillates, petroleum, hydrotreated	>= 10 - <= 25	Not available.
middle		
Titanium dioxide	>= 10 - <= 25	13463-67-7
Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	>= 5 - <= 10	41556-26-7
		1000 04 4
Carbon black	>= 1 - <= 3	1333-86-4
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl	>= 1 - <= 3	82919-37-7
ester		

ne.

HAZEL DOOR, ISO-FIX COVER

Version Number 1.0 Revision Date 10/13/2020 Page 3 of 18 Print Date 10/16/2020

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.



HAZEL DOOR, ISO-FIX COVER

Version Number 1.0 Revision Date 10/13/2020 Page 4 of 18 Print Date 10/16/2020

Most important symptoms/effects, acute and delayed

Potential acute health effects	
Inhalation Skin contact	 No known significant effects or critical hazards. No known significant effects or critical hazards. Causes skin irritation. May cause an allergic skin reaction. No known significant effects or critical hazards.
Over-exposure signs/symptoms	
Eye contact	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	No specific data.
Indication of immediate medical atten	tion and special treatment needed, if necessary
Notes to physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	No specific treatment.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or $\rm CO_2$. None known.
Specific hazards arising from the chemical	:	In a fire or if heated, a pressure increase will occur and the container may burst.

PolyOne.

HAZEL DOOR, ISO-FIX COVER

Version Number 1.0 Revision Date 10/13/2020 Page 5 of 18 Print Date 10/16/2020

Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Environmental precautions:Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).Methods and materials for containment and cleaning upSmall spill:Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water- insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.Large spill:Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to	For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
 Small spill Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. Large spill Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or 		:	waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
 water and mop up if water-soluble. Alternatively, or if water- insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or 	Methods and materials for containing	ent a	nd cleaning up
release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or	Small spill	:	water and mop up if water-soluble. Alternatively, or if water- insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal
	Large spill	:	release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or

'One

HAZEL DOOR, ISO-FIX COVER

Version Number 1.0 Revision Date 10/13/2020 Page 6 of 18 Print Date 10/16/2020

local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Miscellaneous Compounds Distillates, petroleum, hydrotreated middle	None.
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust



HAZEL DOOR, ISO-FIX COVER

Version Number 1.0 Revision Date 10/13/2020

Page 7 of 18 Print Date 10/16/2020

	OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (1996-05-18) TWA 10 mg/m3
Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	None.
Carbon black	OSHA PEL 1989 (1989-03-01) TWA 3.5 mg/m3 OSHA PEL (1993-06-30) TWA 3.5 mg/m3 NIOSH REL (1994-06-01) TWA 3.5 mg/m3 NIOSH REL (1994-06-01) TWA 0.1 mgPAH/m ³ ACGIH TLV (2010-12-06) TWA 3 mg/m3 Form: Inhalable fraction
Decanedioic acid, methyl 1,2,2,6,6- pentamethyl-4-piperidinyl ester	None.

Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
		7/18

<u>PolyOne</u>

HAZEL DOOR, ISO-FIX COVER

Version Number 1.0 Revision Date 10/13/2020

Page 8 of 18 Print Date 10/16/2020

Skin protection

Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state	:	liquid [liquid]
Color	:	BROWN
Odor	:	Faint odor.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.



HAZEL DOOR, ISO-FIX COVER

Version Number 1.0 Revision Date 10/13/2020 Page 9 of 18 Print Date 10/16/2020

Solubility Solubility in water	:	Not available. insoluble in water.
Partition coefficient: n-	:	Not available.
octanol/water		
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	Dynamic: Not available.
-		Kinematic: Not available.
<u>Aerosol product</u> Heat of combustion	:	Not available.
Heat of combustion	:	Not available. Not available.
Heat of combustion Ignition distance Enclosed space ignition - Time		
Heat of combustion Ignition distance Enclosed space ignition - Time equivalent Enclosed space ignition -	:	Not available.
Heat of combustion Ignition distance Enclosed space ignition - Time equivalent	:	Not available. Not available.
Heat of combustion Ignition distance Enclosed space ignition - Time equivalent Enclosed space ignition -	:	Not available. Not available.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Keep away from strong acids. Oxidizer.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity				
Product/ingredient name	Result	Species	Dose	Exposure
Titanium oxide				
		- / / -		



HAZEL DOOR, ISO-FIX COVER

Version Number 1.0 Revision Date 10/13/2020

Page 10 of 18 Print Date 10/16/2020

	LC50 Inhalation Dusts and mists	Rat - Male	6.82 Mg/l	4 h
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-
Carbon black				
	LD50 Oral	Rat	15,400 mg/kg	-

Conclusion/Summary

: Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result		Species	Score	Exposure	Observation
Titanium oxide	Skin - Mild irr	itant	Human	-	72 hrs	-
Conclusion/Summary						
Skin	: M	ixture.Not f	fully tested.			
Eyes	: M	ixture.Not f	fully tested.			
Respiratory	: M	ixture.Not f	fully tested.			
Sensitization						
Conclusion/Summary						
Skin		ixture.Not f				
Respiratory	: M	ixture.Not f	fully tested.			
<u>Mutagenicity</u>						
Conclusion/Summary	: M	ixture.Not f	fully tested.			
Carcinogenicity						
Conclusion/Summary	: M	ixture.Not f	fully tested.			
Classification						
Product/ingredient name	OSHA	IARC	NTP			
Titanium oxide	-	2B	-			
Carbon black	-	2B	-			

Conclusion/Summary	:	Mixture.Not fully tested.
--------------------	---	---------------------------

Teratogenicity

Conclusion/Summary Mixture.Not fully tested. :

10/18

PolyOne

HAZEL DOOR, ISO-FIX COVER

Version Number 1.0 Revision Date 10/13/2020

Page 11 of 18 Print Date 10/16/2020

Specific target organ toxicity (single exposure) Not available.

Specific target organ toxicity (repeated exposure) Not available.

Aspiration hazard

Name		Result		
Miscellaneous Compounds Distillates, hydrotreated middle	, petroleum,	ASPIRATION HAZARD - Category 1		
Information on the likely routes of exposure	: Not avai	ilable.		
Potential acute health effects				
Eye contact	: No know	vn significant effects or critical hazards.		
Inhalation		wn significant effects or critical hazards.		
Skin contact		skin irritation. May cause an allergic skin reaction.		
Ingestion	: No know	wn significant effects or critical hazards.		
Commentance related to the physical of		vision and the vester initian		
Symptoms related to the physical, cl	nemical and to	<u>oxicological characteristics</u>		
Eye contact	: Adverse	symptoms may include the following: pain or irritation,		
	watering	g, redness		
Inhalation	: No speci	No specific data.		
Skin contact	: Adverse	Adverse symptoms may include the following: irritation, redness		
Ingestion	: No speci	ific data.		
Delayed and immediate effects and a	also chronic ef	fects from short and long term exposure		
<u>Short term exposure</u>				
Potential immediate effects	: Not avai	ilable.		
Potential delayed effects	Not avai			
Long term exposure				
Potential immediate effects	: Not avai	ilable.		
Potential delayed effects	Not avai			
-				
Potential chronic health effects				



HAZEL DOOR, ISO-FIX COVER

Version Number 1.0 Revision Date 10/13/2020 Page 12 of 18 Print Date 10/16/2020

Conclusion/Summary	:	Mixture.Not fully tested.
General	:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	No known significant effects or critical hazards.
Developmental effects	:	No known significant effects or critical hazards.
Fertility effects	:	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
HAZEL DOOR, ISO-FIX COVER	52,079 mg/kg	N/A	N/A	92.4 Mg/l	N/A
Miscellaneous Compounds Distillates, petroleum, hydrotreated middle	N/A	N/A	N/A	11 Mg/l	N/A
Titanium oxide	N/A	N/A	N/A	N/A	6.82 Mg/l
Carbon black	15,400 mg/kg	N/A	N/A	N/A	N/A

Other information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Section 12. Ecological information

:

Toxicity

Product/ingredient name	Result	Species	Exposure		
Titanium oxide					
	Acute LC50 > 1,000 Mg/l	Fish - Fundulus heteroclitus	96 h		
	Marine water				
	Acute LC50 3 Mg/l Fresh water	Crustaceans - Ceriodaphnia	48 h		
		dubia			
40/40					



HAZEL DOOR, ISO-FIX COVER

Version Number 1.0 Revision Date 10/13/2020

Page 13 of 18 Print Date 10/16/2020

	Acute LC50 6.5 Mg/l Fresh water	Daphnia - Daphnia pulex	48 h
Carbon black			
	Acute EC50 37.563 Mg/l Fresh water	Daphnia - Daphnia magna	48 h
Conclusion/Summary	: Not available.		
Persistence and degradability	<u>'</u>		
Conclusion/Summary	: Not available.		
<u>Bioaccumulative potential</u> Not available.			
Mobility in soil			
Soil/water partition coefficie (KOC)	ent : Not available.		
Other adverse effects	: No known significant e	effects or critical hazards.	

Section 13. Disposal considerations

The generation of waste should be avoided or minimized wherever **Disposal methods** : possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

<u>lyOne</u>

HAZEL DOOR, ISO-FIX COVER

Version Number 1.0 Revision Date 10/13/2020 Page 14 of 18 Print Date 10/16/2020

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	: Not regulated for transportation.
International Air ICAO/IATA	: Not classified as dangerous goods under transport regulations.
International Water IMO/IMDG	: Not classified as dangerous goods under transport regulations.

Section 15. Regulatory information

U.S. Federal regulations	: United States - TSCA 12(b) - Chemical export notification: None of the components are listed.
	United States - TSCA 4(a) - Final Test Rules: Not listed
	United States - TSCA 4(a) - ITC Priority list: Not listed
	United States - TSCA 4(a) - Proposed test rules: Not listed
	United States - TSCA 4(f) - Priority risk review: Not listed
	United States - TSCA 5(a)2 - Final significant new use rules: Not
	listed
	United States - TSCA 5(a)2 - Proposed significant new use rules:
	Not listed
	United States - TSCA 5(e) - Substances consent order: Not listed
	United States - TSCA 6 - Final risk management: Not listed
	United States - TSCA 6 - Proposed risk management: Not listed
	United States - TSCA 8(a) - Chemical risk rules: Not listed
	United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed
	United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined
	United States - TSCA 8(a) - Preliminary assessment report
	(PAIR): Not listed
	United States - TSCA 8(c) - Significant adverse reaction (SAR):
	Not listed
	United States - TSCA 8(d) - Health and safety studies: Not listed
	United States - EPA Clean water act (CWA) section 307 - Priority
	pollutants: Listed Rutile, antimony chromium buff
	Zinc ferrite brown spinel (C.I. Pigment Yellow 119)
	United States - FPA Clean water act (CWA) section 311 -

United States - EPA Clean water act (CWA) section 311 -

ne

HAZEL DOOR, ISO-FIX COVER

Version Number 1.0 Revision Date 10/13/2020 Page 15 of 18 Print Date 10/16/2020

Hazardous substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed

Clean Air Act Section 112(b)	:	Listed
Hazardous Air Pollutants (HAPs) Clean Air Act Section 602 Class I	:	Not listed
Substances Clean Air Act Section 602 Class II	:	Not listed
Substances DEA List I Chemicals (Precursor	:	Not listed
Chemicals) DEA List II Chemicals (Essential	:	Not listed
Chemicals)		

US. EPA CERCLA Hazardous Substances (40 CFR 302)

:

not applicable

SARA 311/312

Classification

SKIN IRRITATION - Category 2 SKIN SENSITIZATION - Category 1

Composition/information on ingredients

Name	%	Classification
Miscellaneous Compounds	>= 10 - <= 25	ACUTE TOXICITY - inhalation - Category 4
Distillates, petroleum,		SKIN IRRITATION - Category 2
hydrotreated middle		ASPIRATION HAZARD - Category 1
Titanium oxide	>= 10 - <= 25	CARCINOGENICITY - Category 2
Decanedioic acid, 1,10- bis(1,2,2,6,6-pentamethyl-4- piperidinyl) ester	>= 5 - <= 10	SKIN SENSITIZATION - Category 1
Carbon black	>= 1 - <= 3	CARCINOGENICITY - Category 2
Decanedioic acid, 1-methyl 10-(1,2,2,6,6-pentamethyl- 4-piperidinyl) ester	>= 1 - <= 3	SKIN SENSITIZATION - Category 1



HAZEL DOOR, ISO-FIX COVER

Version Number 1.0 Revision Date 10/13/2020 Page 16 of 18 Print Date 10/16/2020

Form R - Reporting requirements

Product name	CAS number	%
Rutile, antimony chromium buff	68186-90-3	>= 10 - <= 25
Zinc ferrite brown spinel (C.I. Pigment Yellow 119)	68187-51-9	>= 3 - <= 5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

Not applicable.

State regulations	
Massachusetts	: None of the components are listed.
New York	: None of the components are listed.
New Jersey	: The following components are listed: Iron oxide Rutile, antimony chromium buff Titanium dioxide Zinc ferrite brown spinel (C.I. Pigment Yellow 119) Carbon black
Pennsylvania	: The following components are listed:
1 onnsylvania	Iron oxide
	Rutile, antimony chromium buff
	Titanium dioxide
	Zinc ferrite brown spinel (C.I. Pigment Yellow 119)
	Carbon black

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Titanium dioxide	-	-
Carbon black	-	-

HAZEL DOOR, ISO-FIX COVER

Version Number 1.0 Revision Date 10/13/2020 Page 17 of 18 Print Date 10/16/2020

United States inventory (TSCA 8b)	:	All components are active or exempted.
Canada inventory	:	All components are listed or exempted.
International regulations		
<u>Inventory list</u>		
Australia	:	All components are listed or exempted.
Canada	:	All components are listed or exempted.
China	:	All components are listed or exempted.
Europe inventory	:	All components are listed or exempted.
Japan	:	Not determined.
New Zealand	:	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	Not determined.
Turkey	:	Not determined.
United States	:	All components are active or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	2
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

		10/16/2020
Date of printing	:	10/16/2020
Date of issue/Date of revision	:	10/13/2020
Date of previous issue	:	00/00/0000
Version	:	1.0
Key to abbreviations	:	ATE = Acute Toxicity Estimate
-		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of



HAZEL DOOR, ISO-FIX COVER

Version Number 1.0 Revision Date 10/13/2020 Page 18 of 18 Print Date 10/16/2020

Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations Not available.

References

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.