# HAZEL DOOR, ISO FIX COVER V2

Version Number 1.0 Revision Date 11/04/2020



Page 1 of 17 Print Date 11/05/2020

# SAFETY DATA SHEET

### HAZEL DOOR, ISO FIX COVER V2

Section 1. Identification	on	
GHS product identifier Chemical name CAS number Other means of identification Product type	:	HAZEL DOOR, ISO FIX COVER V2 Mixture Mixture CC10333156 liquid
<u>Relevant identified uses of the subs</u> Product use	tance :	e or mixture and uses advised against Industrial applications. Plastics.
Supplier's details	:	POLYONE CORPORATION ColorMatrix Group Inc. 680 North Rocky River Drive, Berea, Ohio, 44017-1628, USA
		+1 216 622 0100
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

# Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	SKIN SENSITIZATION - Category 1

#### **GHS label elements**

# HAZEL DOOR, ISO FIX COVER V2



Version Number 1.0 Revision Date 11/04/2020 Page 2 of 17 Print Date 11/05/2020

Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	May cause an allergic skin reaction.
Precautionary statements		
	:	Not applicable.
Prevention	:	Wear protective gloves. Avoid breathing vapor.
Response	:	Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known.
		Not available.

# Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	CC10333156

CAS number/other identifiers

Ingredient name	%	CAS number
Titanium dioxide	>= 5 - <= 10	13463-67-7
Miscellaneous Compounds Distillates, petroleum, hydrotreated middle	>= 5 - < 10	Not available.
Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	>= 5 - <= 10	41556-26-7
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester	>= 1 - <= 3	82919-37-7
Carbon black	>= 0.3 - <= 1	1333-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

# There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require

# HAZEL DOOR, ISO FIX COVER V2

Version Number 1.0 Revision Date 11/04/2020 **ÀVIENT** 

Page 3 of 17 Print Date 11/05/2020

reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# **Section 4. First aid measures**

#### **Description of necessary first aid measures**

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

# HAZEL DOOR, ISO FIX COVER V2



Version Number 1.0 Revision Date 11/04/2020 Page 4 of 17 Print Date 11/05/2020

Eye contact Inhalation Skin contact Ingestion	<ul> <li>No known significant effects or critical hazards.</li> <li>No known significant effects or critical hazards.</li> <li>May cause an allergic skin reaction.</li> <li>No known significant effects or critical hazards.</li> </ul>
Over-exposure signs/symptoms	
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Indication of immediate medica	ttention and special treatment needed, if necessary
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# **Section 5. Fire-fighting measures**

#### **Extinguishing media**

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or $CO_2$ . None known.
Specific hazards arising from the chemical Hazardous thermal decomposition products	:	In a fire or if heated, a pressure increase will occur and the container may burst. Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

# HAZEL DOOR, ISO FIX COVER V2



Version Number 1.0 Revision Date 11/04/2020 Page 5 of 17 Print Date 11/05/2020

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	
Methods and materials for containment	Methods and materials for containment and cleaning up		
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.	

# Section 7. Handling and storage

#### Precautions for safe handling

# HAZEL DOOR, ISO FIX COVER V2

Version Number 1.0 Revision Date 11/04/2020



Page 6 of 17 Print Date 11/05/2020

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (1996-05-18) TWA 10 mg/m3
Miscellaneous Compounds Distillates, petroleum, hydrotreated middle	None.
Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	None.
Decanedioic acid, methyl 1,2,2,6,6- pentamethyl-4-piperidinyl ester	None.
Carbon black	OSHA PEL 1989 (1989-03-01)

# HAZEL DOOR, ISO FIX COVER V2

Version Number 1.0 Revision Date 11/04/2020



Page 7 of 17 Print Date 11/05/2020

		TWA 3.5 mg/m3 <b>OSHA PEL (1993-06-30)</b> TWA 3.5 mg/m3 <b>NIOSH REL (1994-06-01)</b> TWA 3.5 mg/m3 <b>NIOSH REL (1994-06-01)</b> TWA 0.1 mgPAH/m <sup>3</sup> <b>ACGIH TLV (2010-12-06)</b> TWA 3 mg/m3 Form: Inhalable fraction
Appropriate engineering controls Environmental exposure controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures Eye/face protection	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

# HAZEL DOOR, ISO FIX COVER V2



Version Number 1.0 Revision Date 11/04/2020

#### Page 8 of 17 Print Date 11/05/2020

Body protection	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

#### **Appearance**

Physical state	:	liquid [liquid]
Color	:	BROWN
Odor	:	Faint odor.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		<b>Upper:</b> Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	insoluble in water.
Partition coefficient: n-	:	Not available.
octanol/water		
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	<b>Dynamic:</b> Not available.
		Kinematic: Not available.

Aerosol product

# HAZEL DOOR, ISO FIX COVER V2

Version Number 1.0 Revision Date 11/04/2020



Page 9 of 17 Print Date 11/05/2020

Heat of combustion	:	Not available.
Ignition distance	:	Not available.
Enclosed space ignition - Time	:	Not available.
equivalent		
Enclosed space ignition -	:	Not available.
Deflagration density		
Flame height	:	Not available.
Flame duration	:	Not available.

# Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Keep away from strong acids. Oxidizer.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

Acute toxicity				
Product/ingredient name	Result	Species	Dose	Exposure
Titanium oxide				
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h
	Dusts and mists		_	
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-
Carbon black				
	LD50 Oral	Rat	15,400 mg/kg	-

Conclusion/Summary

: Mixture.Not fully tested.

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium oxide	Skin - Mild irritant	Human	-	72 hrs	-

# HAZEL DOOR, ISO FIX COVER V2



Version Number 1.0 Revision Date 11/04/2020

Page 10 of 17 Print Date 11/05/2020

Conclusion/Summary Skin Eyes Respiratory	<ul><li>Mixture.Not fully tested.</li><li>Mixture.Not fully tested.</li><li>Mixture.Not fully tested.</li></ul>
<u>Sensitization</u>	
Conclusion/Summary Skin Respiratory	<ul><li>Mixture.Not fully tested.</li><li>Mixture.Not fully tested.</li></ul>
Mutagenicity	
Conclusion/Summary	: Mixture.Not fully tested.
<b>Carcinogenicity</b>	
Conclusion/Summary	: Mixture.Not fully tested.

#### Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium oxide	-	2B	-
Carbon black	-	2B	-

#### **Reproductive toxicity**

#### **Teratogenicity**

Conclusion/Summary	:	Mixture.Not fully tested.
--------------------	---	---------------------------

# Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure) Not available.

#### **Aspiration hazard**

Name	Result
Miscellaneous Compounds Distillates, petroleum,	ASPIRATION HAZARD - Category 1
hydrotreated middle	

#### Information on the likely routes of : Not available. exposure

# HAZEL DOOR, ISO FIX COVER V2



Version Number 1.0 Revision Date 11/04/2020 Page 11 of 17 Print Date 11/05/2020

Potential acute health effects		
Eye contact Inhalation Skin contact Ingestion	::	No known significant effects or critical hazards. No known significant effects or critical hazards. May cause an allergic skin reaction. No known significant effects or critical hazards.
Symptoms related to the physical, ch	emi	cal and toxicological characteristics
Eye contact Inhalation Skin contact Ingestion	::	No specific data. No specific data. Adverse symptoms may include the following: irritation, redness No specific data.
Delayed and immediate effects and a	lso	chronic effects from short and long term exposure
Short term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Long term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.
General	:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity Mutagenicity Teratogenicity Developmental effects Fertility effects	:::::::::::::::::::::::::::::::::::::::	No known significant effects or critical hazards. No known significant effects or critical hazards.

#### Numerical measures of toxicity

#### Acute toxicity estimates

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
		•			



# HAZEL DOOR, ISO FIX COVER V2

Version Number 1.0 Revision Date 11/04/2020

#### Page 12 of 17 Print Date 11/05/2020

HAZEL DOOR, ISO FIX COVER V2	52,080.6 mg/kg	N/A	N/A	117.4 Mg/l	N/A
Titanium oxide	N/A	N/A	N/A	N/A	6.82 Mg/l
Miscellaneous Compounds Distillates, petroleum, hydrotreated middle	N/A	N/A	N/A	11 Mg/l	N/A
Carbon black	15,400 mg/kg	N/A	N/A	N/A	N/A

#### Other information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

# Section 12. Ecological information

:

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure	
Titanium oxide				
	Acute LC50 > 1,000 Mg/l Marine water	Fish - Fundulus heteroclitus	96 h	
	Acute LC50 3 Mg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 h	
	Acute LC50 6.5 Mg/l Fresh water	Daphnia - Daphnia pulex	48 h	
Carbon black				
	Acute EC50 37.563 Mg/l Fresh water	Daphnia - Daphnia magna	48 h	
HAZEL DOOR, ISO FIX COVER V2				
Remarks - Acute - Aquatic invertebrates.:				

**Conclusion/Summary** 

Dangerous for the environment: May cause long term adverse effects in the aquatic environment.

#### Persistence and degradability

**Conclusion/Summary** 

Not available.

:

:

# HAZEL DOOR, ISO FIX COVER V2

Version Number 1.0 Revision Date 11/04/2020



Page 13 of 17 Print Date 11/05/2020

Conclusion/Summary	:	Dangerous for the environment: May cause long term adverse effects in the aquatic environment.
Bioaccumulative potential Not available.		
<u>Mobility in soil</u>		
Soil/water partition coefficient (KOC)	:	Not available.
Other adverse effects		No known significant effects or critical hazards

# Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

# Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	: Not regulated for transportation.
International Air ICAO/IATA	: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate), 9, PGIII, Marine Pollutant
International Water	: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
	13/17

# HAZEL DOOR, ISO FIX COVER V2

Version Number 1.0 Revision Date 11/04/2020

# **ÀVIENT**

Page 14 of 17 Print Date 11/05/2020

IMO/IMDG

LIQUID, N.O.S. (Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate), 9, PGIII, Marine Pollutant

# Section 15. Regulatory information

U.S. Federal regulations	:	<ul> <li>United States - TSCA 12(b) - Chemical export notification: None of the components are listed.</li> <li>United States - TSCA 4(a) - Final Test Rules: Not listed</li> <li>United States - TSCA 4(a) - ITC Priority list: Not listed</li> <li>United States - TSCA 4(a) - Proposed test rules: Not listed</li> <li>United States - TSCA 4(a) - Proposed test rules: Not listed</li> <li>United States - TSCA 5(a) - Proposed significant new use rules: Not listed</li> <li>United States - TSCA 5(a) - Proposed significant new use rules: Not listed</li> <li>United States - TSCA 5(a) - Proposed significant new use rules: Not listed</li> <li>United States - TSCA 5(a) - Proposed significant new use rules: Not listed</li> <li>United States - TSCA 5(a) - Proposed risk management: Not listed</li> <li>United States - TSCA 6 - Final risk management: Not listed</li> <li>United States - TSCA 8(a) - Chemical risk rules: Not listed</li> <li>United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed</li> <li>United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined</li> <li>United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed</li> <li>United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed</li> <li>United States - TSCA 8(c) - Health and safety studies: Not listed</li> <li>United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Rutile, antimony chromium buff</li> <li>United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed</li> <li>United States - Department of commerce - Precursor chemical: Not listed</li> </ul>
Clean Air Act Section 112(b)	:	Listed
Hazardous Air Pollutants (HAPs)	•	
Clean Air Act Section 602 Class I Substances	:	Not listed
Clean Air Act Section 602 Class II Substances	:	Not listed
DEA List I Chemicals (Precursor	:	Not listed

# HAZEL DOOR, ISO FIX COVER V2

Version Number 1.0 Revision Date 11/04/2020 Page 15 of 17 Print Date 11/05/2020

**& AVIENT**"

Chemicals) DEA List II Chemicals (Essential : Not listed Chemicals)

#### US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

#### SARA 311/312

Classification

: SKIN SENSITIZATION - Category 1

#### **Composition/information on ingredients**

Name	%	Classification
Titanium oxide	>= 5 - <= 10	CARCINOGENICITY - Category 2
Miscellaneous Compounds Distillates, petroleum, hydrotreated middle	>= 5 - < 10	ACUTE TOXICITY - inhalation - Category 4 SKIN IRRITATION - Category 2 ASPIRATION HAZARD - Category 1
Decanedioic acid, 1,10- bis(1,2,2,6,6-pentamethyl-4- piperidinyl) ester	>= 5 - <= 10	SKIN SENSITIZATION - Category 1
Decanedioic acid, 1-methyl 10-(1,2,2,6,6-pentamethyl- 4-piperidinyl) ester	>= 1 - <= 3	SKIN SENSITIZATION - Category 1
Carbon black	>= 0.3 - <= 1	CARCINOGENICITY - Category 2

#### Form R - Reporting requirements

Product name	CAS number	%
Rutile, antimony chromium buff	68186-90-3	>= 25 - <= 50

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

Not applicable.

<u>State regulations</u> Massachusetts New York New Jersey	<ul><li>None of the components are listed.</li><li>None of the components are listed.</li><li>The following components are listed:</li></ul>
---	--

# HAZEL DOOR, ISO FIX COVER V2

Version Number 1.0 Revision Date 11/04/2020



Page 16 of 17 Print Date 11/05/2020

	Rutile, antimony chromium buff
	Titanium dioxide
	Iron oxide
	Carbon black
:	The following components are listed:
	Rutile, antimony chromium buff
	Titanium dioxide
	Iron oxide

Carbon black

#### California Prop. 65

Pennsylvania

**WARNING:** This product can expose you to chemicals including Titanium dioxide, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Titanium dioxide	-	-
Carbon black	-	-

Childed Blattes inventory (1964 06) • The components are derive or exempted	United States inventory (TSCA 8b)	:	All components are active or exempted.
---	-----------------------------------	---	--

:

**Canada inventory** 

All components are listed or exempted.

International	regulations
meenman	regulations

**Inventory list** 

# Section 16. Other information

# HAZEL DOOR, ISO FIX COVER V2

Version Number 1.0 Revision Date 11/04/2020 **ÀVIENT** 

Page 17 of 17 Print Date 11/05/2020

#### Hazardous Material Information System (U.S.A.)

Health	/	2
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

<b>Histor</b>		
Date of printing	:	11/05/2020
Date of issue/Date of revision	:	11/04/2020
Date of previous issue	:	00/00/0000
Version	:	1.0
Key to abbreviations	:	ATE = Acute Toxicity Estimate
•		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From
		Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)
		UN = United Nations
References	:	Not available.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.