## HAZEL ISO FIX DOOR V3

Version Number 1.0 Revision Date 01/12/2021



Page 1 of 17 Print Date 01/13/2021

# SAFETY DATA SHEET

### HAZEL ISO FIX DOOR V3

Section 1. Identification			
GHS product identifier Chemical name CAS number Other means of identification Product type	:	HAZEL ISO FIX DOOR V3 Mixture Mixture CC10335931 liquid	
Relevant identified uses of the substance or mixture and uses advised againstProduct use:Industrial applications. Plastics.			
Supplier's details	:	<b>POLYONE CORPORATION</b> ColorMatrix Group Inc. 680 North Rocky River Drive, Berea, Ohio, 44017-1628, USA	
		+1 216 622 0100	
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).	

# Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	SKIN SENSITIZATION - Category 1

#### **GHS label elements**

# HAZEL ISO FIX DOOR V3

Version Number 1.0 Revision Date 01/12/2021



#### Page 2 of 17 Print Date 01/13/2021

Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	May cause an allergic skin reaction.
Precautionary statements		
Prevention	:	Not applicable. Wear protective gloves. Avoid breathing vapor.
Response	:	Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known. Not available.

# Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	CC10335931

CAS number/other identifiers

Ingredient name	%	CAS number
Titanium dioxide	>= 10 - <= 25	13463-67-7
Miscellaneous Compounds Distillates, petroleum, hydrotreated middle	>= 5 - < 10	Not available.
Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	>= 5 - <= 10	41556-26-7
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester	>= 1 - <= 3	82919-37-7
Carbon black	>= 0.3 - <= 1	1333-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

# There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require

# HAZEL ISO FIX DOOR V3

Version Number 1.0 Revision Date 01/12/2021



Page 3 of 17 Print Date 01/13/2021

reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# **Section 4. First aid measures**

#### **Description of necessary first aid measures**

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

# HAZEL ISO FIX DOOR V3

Version Number 1.0 Revision Date 01/12/2021



Page 4 of 17 Print Date 01/13/2021

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/symptoms	
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation
	redness
Ingestion	: No specific data.
Indication of immediate medica	attention and special treatment needed, if necessary
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# **Section 5. Fire-fighting measures**

#### Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or $CO_2$ . None known.
Specific hazards arising from the chemical Hazardous thermal decomposition products	:	In a fire or if heated, a pressure increase will occur and the container may burst. Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. 4/17

# HAZEL ISO FIX DOOR V3

Version Number 1.0 Revision Date 01/12/2021

# **ÀVIENT**

Page 5 of 17 Print Date 01/13/2021

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containment	nt aı	nd cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

# HAZEL ISO FIX DOOR V3

# **ÀVIENT**

Version Number 1.0	Page 6 of 17
Revision Date 01/12/2021	Print Date 01/13/2021

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits	
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (1996-05-18) TWA 10 mg/m3	
Miscellaneous Compounds Distillates, petroleum, hydrotreated middle	None.	
Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	None.	
Decanedioic acid, methyl 1,2,2,6,6- pentamethyl-4-piperidinyl ester	None.	
Carbon black	OSHA PEL 1989 (1989-03-01)	
6/17		

# HAZEL ISO FIX DOOR V3


Version Number 1.0 Revision Date 01/12/2021



Page 7 of 17
Print Date 01/13/2021

		TWA 3.5 mg/m3 OSHA PEL (1993-06-30) TWA 3.5 mg/m3 NIOSH REL (1994-06-01) TWA 3.5 mg/m3 NIOSH REL (1994-06-01) TWA 0.1 mgPAH/m <sup>3</sup> ACGIH TLV (2010-12-06) TWA 3 mg/m3 Form: Inhalable fraction
Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

# HAZEL ISO FIX DOOR V3



# **ÀVIENT**

Version Number 1.0	Page 8 of 17
Revision Date 01/12/2021	Print Date 01/13/2021

Body protection	: Personal protective equipment for the body should be selected on the task being performed and the risks involved and should approved by a specialist before handling this product.	
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection meas should be selected based on the task being performed and the involved and should be approved by a specialist before handli product.</li> </ul>	risks
Respiratory protection	: Based on the hazard and potential for exposure, select a respin meets the appropriate standard or certification. Respirators mu used according to a respiratory protection program to ensure p fitting, training, and other important aspects of use.	ust be

# Section 9. Physical and chemical properties

#### Appearance

Physical state	:	liquid [liquid]
Color	:	BROWN
Odor	:	Faint odor.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	insoluble in water.
Partition coefficient: n- octanol/water	:	Not available.
Auto-ignition temperature		Not available.
Decomposition temperature		Not available.
SADT		Not available.
Viscosity		<b>Dynamic:</b> Not available.
viscosity	•	<b>Kinematic:</b> Not available.

Aerosol product

# HAZEL ISO FIX DOOR V3

Version Number 1.0 Revision Date 01/12/2021

# **ÀVIENT**

Page 9 of 17
Print Date 01/13/2021

Heat of combustion	:	Not available.
Ignition distance	:	Not available.
Enclosed space ignition - Time equivalent	:	Not available.
Enclosed space ignition -	:	Not available.
Deflagration density		
Flame height	:	Not available.
Flame duration	:	Not available.

# Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Keep away from strong acids. Oxidizer.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

Acute toxicity				
Product/ingredient name	Result	Species	Dose	Exposure
Titanium oxide				
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h
	Dusts and mists			
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-
Carbon black				
	LD50 Oral	Rat	15,400 mg/kg	-

Conclusion/Summary

: Mixture.Not fully tested.

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium oxide	Skin - Mild irritant	Human	-	72 hrs	-

# HAZEL ISO FIX DOOR V3

Version Number 1.0 Revision Date 01/12/2021



Page 10 of 17
Print Date 01/13/2021

Conclusion/Summary Skin Eyes Respiratory	<ul><li>Mixture.Not fully tested.</li><li>Mixture.Not fully tested.</li><li>Mixture.Not fully tested.</li></ul>
<b>Sensitization</b>	
Conclusion/Summary Skin Respiratory	<ul><li>Mixture.Not fully tested.</li><li>Mixture.Not fully tested.</li></ul>
<b>Mutagenicity</b>	
Conclusion/Summary	: Mixture.Not fully tested.
<b>Carcinogenicity</b>	
Conclusion/Summary	: Mixture.Not fully tested.

#### Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium oxide	-	2B	-
Carbon black	-	2B	-

#### **Reproductive toxicity**

Conclusion/Summary	:	Mixture.Not fully tested.
--------------------	---	---------------------------

#### **Teratogenicity**

#### <u>Specific target organ toxicity (single exposure)</u> Not available

Not available.

#### Specific target organ toxicity (repeated exposure) Not available.

#### Aspiration hazard

Name	Result
Miscellaneous Compounds Distillates, petroleum,	ASPIRATION HAZARD - Category 1
hydrotreated middle	

# **Information on the likely routes of** : Not available. **exposure**

# HAZEL ISO FIX DOOR V3

Version Number 1.0 Revision Date 01/12/2021



#### Page 11 of 17 Print Date 01/13/2021

Potential acute health effects		
Eye contact Inhalation Skin contact Ingestion Symptoms related to the physical, c	No known significant effects or critical hazards. No known significant effects or critical hazards. May cause an allergic skin reaction. No known significant effects or critical hazards. <b>mical and toxicological characteristics</b>	
Symptoms related to the physical, e	incar and toxicological characteristics	
Eye contact	No specific data.	
Inhalation	No specific data.	
Skin contact	Adverse symptoms may include the following: irritation, red	ness
Ingestion	No specific data.	
	o chronic effects from short and long term exposure	
<u>Short term exposure</u>		
Potential immediate effects Potential delayed effects	Not available. Not available.	
Long term exposure		
Potential immediate effects Potential delayed effects	Not available. Not available.	
Potential chronic health effects		
Conclusion/Summary	Mixture.Not fully tested.	
General	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.	
Carcinogenicity	No known significant effects or critical hazards.	
Mutagenicity	No known significant effects or critical hazards.	
Teratogenicity	No known significant effects or critical hazards.	
<b>Developmental effects</b>	No known significant effects or critical hazards.	
Fertility effects	No known significant effects or critical hazards.	

#### Numerical measures of toxicity

#### Acute toxicity estimates

	nhalation dusts and mists)
--	----------------------------------



# HAZEL ISO FIX DOOR V3

Version Number 1.0 Revision Date 01/12/2021

### Page 12 of 17 Print Date 01/13/2021

HAZEL ISO FIX DOOR V3	52,079.1 mg/kg	N/A	N/A	119.4 Mg/l	N/A
Titanium oxide	N/A	N/A	N/A	N/A	6.82 Mg/l
Miscellaneous Compounds Distillates, petroleum, hydrotreated middle	N/A	N/A	N/A	11 Mg/l	N/A
Carbon black	15,400 mg/kg	N/A	N/A	N/A	N/A

#### Other information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

# Section 12. Ecological information

:

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure		
Titanium oxide					
	Acute LC50 > 1,000 Mg/l Marine water	Fish - Fundulus heteroclitus	96 h		
	Acute LC50 3 Mg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 h		
	Acute LC50 6.5 Mg/l Fresh water	Daphnia - Daphnia pulex	48 h		
Carbon black					
	Acute EC50 37.563 Mg/l Fresh water	Daphnia - Daphnia magna	48 h		
HAZEL ISO FIX DOOR V3					
Remarks - Acute - Aquatic invertebrates.:					

**Conclusion/Summary** 

Dangerous for the environment: May cause long term adverse effects in the aquatic environment.

#### Persistence and degradability

**Conclusion/Summary** 

Not available.

:

:

# HAZEL ISO FIX DOOR V3

Version Number 1.0 Revision Date 01/12/2021

# AVIENT

Page 13 of 17 Print Date 01/13/2021

Conclusion/Summary	:	Dangerous for the environment: May cause long term adverse effects in the aquatic environment.
<b>Bioaccumulative potential</b> Not available.		
<u>Mobility in soil</u>		
Soil/water partition coefficient (KOC)	:	Not available.
Other adverse effects	•	No known significant effects or critical hazards

# Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

# Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	: Not regulated for transportation.
International Air ICAO/IATA	: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate), 9, PGIII, Marine Pollutant
International Water	: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
	13/17

# HAZEL ISO FIX DOOR V3

Version Number 1.0 Revision Date 01/12/2021

# **ÀVIENT**

Page 14 of 17 Print Date 01/13/2021

IMO/IMDG

LIQUID, N.O.S. (Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate), 9, PGIII, Marine Pollutant

# Section 15. Regulatory information

U.S. Federal regulations	:	United States - TSCA 12(b) - Chemical export notification: None of the components are listed. United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not listed United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Rutile, antimony chromium buff United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental
		release prevention - Flammable substances: Not listed
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	:	Listed
Clean Air Act Section 602 Class I Substances	:	Not listed
Clean Air Act Section 602 Class II Substances	:	Not listed
DEA List I Chemicals (Precursor	:	Not listed

# HAZEL ISO FIX DOOR V3

Version Number 1.0 Revision Date 01/12/2021



Page 15 of 17 Print Date 01/13/2021

Chemicals) DEA List II Chemicals (Essential : Not listed Chemicals)

#### US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

#### SARA 311/312

Classification

: SKIN SENSITIZATION - Category 1

#### **Composition/information on ingredients**

Name	%	Classification
Titanium oxide	>= 10 - <= 25	CARCINOGENICITY - Category 2
Miscellaneous Compounds Distillates, petroleum, hydrotreated middle	>= 5 - < 10	ACUTE TOXICITY - inhalation - Category 4 SKIN IRRITATION - Category 2 ASPIRATION HAZARD - Category 1
Decanedioic acid, 1,10- bis(1,2,2,6,6-pentamethyl-4- piperidinyl) ester	>= 5 - <= 10	SKIN SENSITIZATION - Category 1
Decanedioic acid, 1-methyl 10-(1,2,2,6,6-pentamethyl- 4-piperidinyl) ester	>= 1 - <= 3	SKIN SENSITIZATION - Category 1
Carbon black	>= 0.3 - <= 1	CARCINOGENICITY - Category 2

#### Form R - Reporting requirements

Product name	CAS number	%
Rutile, antimony chromium buff	68186-90-3	>= 25 - <= 50

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

Not applicable.

:	None of the components are listed.
:	None of the components are listed.
:	The following components are listed:
	:

# HAZEL ISO FIX DOOR V3

Version Number 1.0 Revision Date 01/12/2021



Page 16 of 17 Print Date 01/13/2021

	Rutile, antimony chromium buff
	Titanium dioxide
	Iron oxide
	Carbon black
:	The following components are listed:
	Rutile, antimony chromium buff
	Titanium dioxide
	Iron oxide

Carbon black

#### California Prop. 65

Pennsylvania

**WARNING:** This product can expose you to chemicals including Titanium dioxide, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Titanium dioxide	-	-
Carbon black	-	-

United States inventory (TSCA 8b)	:	All components are active or exempted.

:

Canada inventory

All components are listed or exempted.

International	regulations
multinational	regulations

**Inventory list** 

# Section 16. Other information



## HAZEL ISO FIX DOOR V3

Version Number 1.0 Revision Date 01/12/2021 Page 17 of 17 Print Date 01/13/2021

#### Hazardous Material Information System (U.S.A.)

~
0
0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

<b>HISCOL</b>		
Date of printing	:	01/13/2021
Date of issue/Date of revision	:	01/12/2021
Date of previous issue	:	00/00/0000
Version	:	1.0
Key to abbreviations	:	ATE = Acute Toxicity Estimate
•		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From
		Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)
		UN = United Nations
References	:	Not available.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.