SM322 SATIN ALUMINUM C1200HF

Version Number 1.0 Revision Date 05/07/2024



Page 1 of 16 Print Date 05/08/2024

SAFETY DATA SHEET

SM322 SATIN ALUMINUM C1200HF

Section 1. Identification		
GHS product identifier		SM322 SATIN ALUMINUM C1200HF
Chemical name	:	Mixture
CAS number		Mixture
Other means of identification		CC10392585
Product type	:	solid
<u>Relevant identified uses of the subs</u> Product use	tance :	e or mixture and uses advised against Industrial applications.
Supplier's details	:	AVIENT CORPORATION 33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (844) 4AVIENT
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.
Classification of the substance or mixture	:	Not classified.
GHS label elements		
Signal word Hazard statements	:	No signal word. No known significant effects or critical hazards.

SM322 SATIN ALUMINUM C1200HF

Version Number 1.0 Revision Date 05/07/2024 Page 2 of 16 Print Date 05/08/2024

Precautionary statements

	:	Not applicable.
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known.
		Not available.

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	CC10392585

CAS number/other identifiers

Ingredient name	%	CAS number
Ethyl benzene	> 0 - <= 0.3	100-41-4
Styrene	> 0 - <= 0.3	100-42-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. In case of

ÄVIENT

SM322 SATIN ALUMINUM C1200HF



Version Number 1.0 Revision Date 05/07/2024

Skin contact Ingestion	:	inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Most important symptoms/effects, a	cute a	and delayed
Potential acute health effects		
Eye contact Inhalation Skin contact Ingestion	::	No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards.
Over-exposure signs/symptoms		
Eye contact Inhalation Skin contact Ingestion	::	No specific data. No specific data. No specific data. No specific data.
Indication of immediate medical at	tentio	on and special treatment needed, if necessary
Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training.
See toxicological information (Secti	on 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or CO ₂ .
Unsuitable extinguishing media	:	None known.

SM322 SATIN ALUMINUM C1200HF

Version Number 1.0 Revision Date 05/07/2024



Page 4 of 16 Print Date 05/08/2024

Specific hazards arising from the chemical	:	No specific fire or explosion hazard.
Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.


Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions Methods and materials for containme	: ont a	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containine	int a	iu cleaning up
Small spill	:	Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

SM322 SATIN ALUMINUM C1200HF





Page 5 of 16 Print Date 05/08/2024

Precautions for safe handling

Protective measures Advice on general occupational hygiene	:	Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Ethyl benzene	OSHA PEL 1989 (1989-03-01) TWA 435 mg/m3 100 ppm STEL 545 mg/m3 125 ppm OSHA PEL (1993-06-30) TWA 435 mg/m3 100 ppm NIOSH REL (1994-06-01) TWA 435 mg/m3 100 ppm STEL 545 mg/m3 125 ppm ACGIH TLV (2010-12-06) Ototoxicant TWA 20 ppm
Styrene	ACGIH TLV (2020-03-01) Ototoxicant TWA 10 ppm STEL 20 ppm NIOSH REL (1994-06-01) TWA 215 mg/m3 50 ppm STEL 425 mg/m3 100 ppm OSHA PEL 1989 (1989-03-01) TWA 215 mg/m3 50 ppm STEL 425 mg/m3 100 ppm

SM322 SATIN ALUMINUM C1200HF



Version Number 1.0 Revision Date 05/07/2024 Page 6 of 16 Print Date 05/08/2024

		OSHA PEL Z2 (1993-06-30) TWA 100 ppm CEIL 200 ppm AMP 600 ppm
Appropriate engineering controls Environmental exposure controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures Eye/face protection	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection		
Hand protection Body protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be
Other skin protection	:	approved by a specialist before handling this product. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

SM322 SATIN ALUMINUM C1200HF

Version Number 1.0 Revision Date 05/07/2024

ÀVIENT

Page 7 of 16 Print Date 05/08/2024

Section 9. Physical and chemical properties

Appearance

Color Odor Odor threshold pH Melting point Boiling point	solid [Pellets.] GREY Faint odor. Not available. Not available. Not available. Not available. Not applicable.
Burning rate Evaporation rate Flammability (solid, gas)	 Not available. Not available. Not available. Not available. Lower: Not applicable. Upper: Not applicable.
	Not available. Not applicable.
Solubility	Not available.Not available.insoluble in water.
octanol/water	Not applicable.Not applicable.
SADT	 Not available. Not available. Dynamic: Not available. Kinematic: Not applicable.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	 Stable under recommended storage and handling conditions (see Section 7).

SM322 SATIN ALUMINUM C1200HF

Version Number 1.0 Revision Date 05/07/2024



Page 8 of 16 Print Date 05/08/2024

Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Keep away from strong acids.
		Oxidizer.
Hazardous decomposition	:	Under normal conditions of storage and use, hazardous decomposition
products		products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Product/ingredient name	Result	Species	Dose	Exposure
Benzene, ethyl-				
	LD50 Oral	Rat	3,500 mg/kg	-
	LD50 Dermal	Rabbit	5,000 mg/kg	-
Styrene		•		
•	LD50 Oral	Rat	2,650 mg/kg	-
	LC50 Inhalation	Rat	2,770 ppm	4 h
	Gas.			
	LC50 Inhalation	Rat	11.8 Mg/l	4 h
	Vapor		_	

Conclusion/Summary

: Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Benzene, ethyl-	Skin - Mild irritant	Rabbit	-	24 hrs	-
	Eyes - Severe irritant	Rabbit	-		-
Styrene	Eyes - Mild irritant	Human	-		-
	Skin - Mild irritant	Rabbit	-		-
	Skin - Moderate irritant	Rabbit	-		-
	Eyes - Severe irritant	Rabbit	-		-
	Eyes - Moderate	Rabbit	-	24 hrs	-
	irritant				

Conclusion/Summary		
Skin	:	Mixture.Not fully tested.
Eyes	:	Mixture.Not fully tested.
Respiratory	:	Mixture.Not fully tested.

Sensitization

SM322 SATIN ALUMINUM C1200HF

Version Number 1.0 Revision Date 05/07/2024



Page 9 of 16 Print Date 05/08/2024

Conclusion/Summary		
Skin	:	Mixture.Not fully tested.
Respiratory	:	Mixture.Not fully tested.
Mutagenicity		
Conclusion/Summary	:	Mixture.Not fully tested.
Carcinogenicity		
Conclusion/Summary	:	Mixture.Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
Benzene, ethyl-	-	2B	-
Styrene	-	2B	Reasonably anticipated to be a human carcinogen.

Reproductive toxicity

Conclusion/Summary	:	Mixture.Not fully tested.
--------------------	---	---------------------------

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Name	Result
Benzene, ethyl-	ASPIRATION HAZARD - Category 1

Information on the likely routes of	:	Not available.
exposure		

Potential acute health effects

Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.

SM322 SATIN ALUMINUM C1200HF

Version Number 1.0 Revision Date 05/07/2024



Page 10 of 16 Print Date 05/08/2024

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	:	No specific data.
Inhalation	:	No specific data.
Skin contact	:	No specific data.
Ingestion	:	No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

<u>Short</u>	term	exposure

Potential immediate effects Potential delayed effects	Not available. Not available.	
Long term exposure		

:

:

:

:

:

:

:

Long term exposure

Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.

Potential chronic health effects

Conclusion/Summary

General Carcinogenicity Mutagenicity Teratogenicity Developmental effects Fertility effects

Numerical measures of toxicity

Acute toxicity estimates

Other information

: This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Section 12. Ecological information

Mixture.Not fully tested.

Not available.

Not available.

No known significant effects or critical hazards.

SM322 SATIN ALUMINUM C1200HF

Version Number 1.0 Revision Date 05/07/2024 **ÀVIENT**™

Page 11 of 16 Print Date 05/08/2024

Toxicity

Product/ingredient name	Result	Species	Exposure		
Benzene, ethyl-					
	Acute LC50 4.2 Mg/l Fresh	Fish - Oncorhynchus mykiss	96 h		
	water				
	Acute EC50 6.53 Mg/l Marine	Crustaceans - Artemia sp.	48 h		
	water	_			
	Acute EC50 2.93 Mg/l Fresh	Daphnia - Daphnia magna	48 h		
	water				
	Acute EC50 4.9 Mg/l Marine	Algae - Skeletonema costatum	72 h		
	water				
	Acute EC50 7.7 Mg/l Marine	Algae - Skeletonema costatum	96 h		
	water				
Styrene					
	Acute LC50 4.02 Mg/l Fresh	Fish - Pimephales promelas	96 h		
	water	~ *			
	Acute EC50 0.0047 Mg/l Fresh	Daphnia - Daphnia magna	48 h		
	water				
	Acute LC50 52 Mg/l Marine	Crustaceans - Artemia salina	48 h		
	water				
	Acute EC50 78 Mg/l Marine	Algae - Skeletonema costatum	96 h		
	water	-			
SM322 SATIN ALUMINUM C	C1200HF				
Remarks - Acute - Aquatic	Chemicals are not readily availa	ble as they are bound within the poly	mer matrix.		
invertebrates.:					
Conclusion/Summary		dily available as they are bound with	hin the		
	polymer matrix.	polymer matrix.			
Persistence and degradability					
Conclusion/Summary		adily available as they are bound wit	thin the		
	polymer matrix.				
Conclusion/Summary	Chamicals are not re	adily available as they are haved with	thin the		
Conclusion/Summary	: Chemicals are not readily available as they are bound within the				
	polymer matrix.				
Bioaccumulative potential					
bioaccumulative potentilar					
Product/ingradiant name	LogDow	BCE Dotontial			

Product/ingredient name	LogPow	BCF	Potential
Benzene, ethyl-	3.6	-	low
Styrene	0.35	13.49	low

SM322 SATIN ALUMINUM C1200HF

Version Number 1.0 Revision Date 05/07/2024



Page 12 of 16 Print Date 05/08/2024

Mobility in soil

Soil/water partition coefficient : Not available. (KOC)

:

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	:	Not regulated for transportation.
International Air ICAO/IATA	:	Not classified as dangerous goods under transport regulations.
International Water IMO/IMDG	:	Not classified as dangerous goods under transport regulations.

Section 15. Regulatory information

U.S. Federal regulations : United States - TSCA 12(b) - Chemical export notification: None of the components are listed.

12/16

SM322 SATIN ALUMINUM C1200HF

Version Number 1.0 Revision Date 05/07/2024



Page 13 of 16 Print Date 05/08/2024

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not listed United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Listed Lead United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Ethyl benzene Lead United States - EPA Clean water act (CWA) section 311 -Hazardous substances: Listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed **United States - Department of commerce - Precursor chemical:** Not listed Listed Not listed

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	:
Clean Air Act Section 602 Class I	:
Substances Clean Air Act Section 602 Class II	:
Substances DEA List I Chemicals (Precursor	
Chemicals)	•
DEA List II Chemicals (Essential Chemicals)	:

Not listed

Not listed

Not listed

SM322 SATIN ALUMINUM C1200HF

Version Number 1.0 Revision Date 05/07/2024



Page 14 of 16 Print Date 05/08/2024

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification

Not applicable.

:

Composition/information on ingredients

No products were found.

Name	%	Classification
Benzene, ethyl-	> 0 - <= 0.3	FLAMMABLE LIQUIDS - Category 3 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2 ASPIRATION HAZARD - Category 1
Styrene	> 0 - <= 0.3	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY - inhalation - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2

SARA 313

Form R - Reporting requirements

Product name	CAS number	%
Aluminum	7429-90-5	>= 5 - < 10
Ethyl benzene	100-41-4	>= 0.1 - < 1
Styrene	100-42-5	>= 0.1 - < 1
Lead	7439-92-1	>= 0 - < 0.1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations Massachusetts

: The following components are listed: Aluminum

14/16

SM322 SATIN ALUMINUM C1200HF

Version Number 1.0 Revision Date 05/07/2024



Page 15 of 16 Print Date 05/08/2024

New York	:	None of the components are listed.
New Jersey	:	The following components are listed:
		Aluminum
		Ethyl benzene
Pennsylvania	:	The following components are listed:
		Aluminum

California Prop. 65

WARNING: This product can expose you to chemicals including Ethyl benzene, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Ethyl benzene	Yes.	-
Styrene	Yes.	-

United States inventory (TSCA 8b)	:	All components are active or exempted.
Canada inventory	:	All components are listed or exempted.
International regulations Inventory list		
Australia	:	All components are listed or exempted.
Canada	:	All components are listed or exempted.
China	:	All components are listed or exempted.
Eurasian Economic Union	:	Russian Federation inventory: Not determined.
Japan	:	Japan inventory (CSCL): Not determined.
		Japan inventory (ISHL): Not determined.
New Zealand	:	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	All components are listed or exempted.
Thailand	:	Not determined.
Turkey	:	Not determined.
United States	:	All components are active or exempted.
Viet Nam	:	Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	0
Flammability		0
Physical hazards		0

SM322 SATIN ALUMINUM C1200HF



Version Number 1.0 Revision Date 05/07/2024 Page 16 of 16 Print Date 05/08/2024

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

<u>Illstol y</u>		
Date of printing	:	05/08/2024
Date of issue/Date of revision	:	05/07/2024
Date of previous issue	:	00/00/0000
Version	:	1.0
Key to abbreviations	:	ATE = Acute Toxicity Estimate
-		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From
		Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)
		UN = United Nations
References	:	Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.