## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019 Page 1 of 22 Print Date 09/03/2019

# SAFETY DATA SHEET

### **2530-HH SAND TOUCH-UP PAINT**

Section 1. Identification	on	
GHS product identifier		2530-HH SAND TOUCH-UP PAINT
Chemical name		Mixture
CAS number	:	Mixture
Other means of identification	:	FO20041974
Product type	:	liquid
<u>Relevant identified uses of the subs</u> Product use	tance :	e or mixture and uses advised against Industrial applications. Plastics.
Supplier's details	:	POLYONE CORPORATION
		33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

## Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2

#### **GHS label elements**



## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019 Page 2 of 22 Print Date 09/03/2019

Hazard pictograms	:	
Signal word Hazard statements	:	Warning Causes serious eye irritation. Causes skin irritation. Suspected of causing cancer.
Precautionary statements		
General Prevention	:	Not applicable. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Wash hands thoroughly after handling.
Response	:	IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	:	Store locked up.
Disposal	:	Dispose of contents and container in accordance with all local,
Supplemental label elements		regional, national and international regulations. None known.
Hazards not otherwise classified	:	None known.

## Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	FO20041974

#### CAS number/other identifiers

Ingredient name	%	CAS number
Methyl ethyl ketone	25 - 50	78-93-3
Tetrahydrofuran	5 - 10	109-99-9



## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019 Page 3 of 22 Print Date 09/03/2019

Titanium dioxide	1 - 3	13463-67-7
Xylenes (o-, m-, p- isomers)	1 - 3	1330-20-7
Ethyl benzene	0 - 0.3	100-41-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get

ne

## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019 Page 4 of 22 Print Date 09/03/2019

medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

### Potential acute health effects

Eye contact Inhalation Skin contact Ingestion	::	Causes serious eye irritation. No known significant effects or critical hazards. Causes skin irritation. No known significant effects or critical hazards.
Over-exposure signs/symptoms		
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Indication of immediate medical atte	ntio	n and special treatment needed, if necessary
Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## **Section 5. Firefighting measures**

#### **Extinguishing media**

Suitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or $CO_2$ .
Unsuitable extinguishing media	:	None known.



## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019 Page 5 of 22 Print Date 09/03/2019

Specific hazards arising from the chemical	:	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	:	May emit Hydrogen Chloride (HCl). Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	
Methods and materials for containment and cleaning up			
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment	
		5/22	

## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019 Page 6 of 22 Print Date 09/03/2019

plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## **Section 7. Handling and storage**

### Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**



## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019 Page 7 of 22 Print Date 09/03/2019

Ingredient name	Exposure limits
Ethyl benzene	OSHA PEL 1989 (1989-03-01) TWA 435 mg/m3 100 ppm STEL 545 mg/m3 125 ppm OSHA PEL (1993-06-30) TWA 435 mg/m3 100 ppm NIOSH REL (1994-06-01) TWA 435 mg/m3 100 ppm STEL 545 mg/m3 125 ppm ACGIH TLV (2010-12-06) TWA 20 ppm
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (1996-05-18) TWA 10 mg/m3
Methyl ethyl ketone	OSHA PEL 1989 (1989-03-01) TWA 590 mg/m3 200 ppm STEL 885 mg/m3 300 ppm OSHA PEL (1993-06-30) TWA 590 mg/m3 200 ppm NIOSH REL (1994-06-01) TWA 590 mg/m3 200 ppm STEL 885 mg/m3 300 ppm ACGIH TLV (1994-09-01) TWA 590 mg/m3 200 ppm STEL 885 mg/m3 300 ppm
Tetrahydrofuran	OSHA PEL 1989 (1989-03-01) TWA 590 mg/m3 200 ppm STEL 735 mg/m3 250 ppm OSHA PEL (1993-06-30) TWA 590 mg/m3 200 ppm NIOSH REL (1994-06-01) TWA 590 mg/m3 200 ppm STEL 735 mg/m3 250 ppm ACGIH TLV (2005-01-01) Absorbed through skin. TWA 50 ppm STEL 100 ppm
Xylenes (o-, m-, p- isomers)	<b>OSHA PEL (1993-06-30)</b> TWA 435 mg/m3 100 ppm

<u>PolyOne</u>

## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019

### Page 8 of 22 Print Date 09/03/2019

Appropriate engineering controls:If user operations generate dust, furnes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.Environmental exposure controls:Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.Individual protection measures:Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.Eye/face protection:Safety eyewar complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worm, unless the assessment indicates a higher degree of protection: chemical splash goggles.Skin protection:Chemical-resistant, impervious gloves complying with an approved standard should be worm at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be orded that the time to breakthrough for any glove material may be <br< th=""><th></th><th></th><th>OSHA PEL 1989 (1989-03-01) TWA 435 mg/m3 100 ppm STEL 655 mg/m3 150 ppm ACGIH TLV (1996-05-18) TWA 434 mg/m3 100 ppm STEL 651 mg/m3 150 ppm</th></br<>			OSHA PEL 1989 (1989-03-01) TWA 435 mg/m3 100 ppm STEL 655 mg/m3 150 ppm ACGIH TLV (1996-05-18) TWA 434 mg/m3 100 ppm STEL 651 mg/m3 150 ppm
Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.Eye/face protection: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.Skin protection: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, 			enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be
Eve/face protectionproducts, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.Eye/face protection: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.Skin protection: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.Body protection: Personal protective equipment for the body should be selected based	Individual protection measures		
<ul> <li>Hand protection</li> <li>Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.</li> <li>Body protection</li> </ul>			products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a
<ul> <li>standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.</li> <li>Body protection : Personal protective equipment for the body should be selected based</li> </ul>	Skin protection		
	Hand protection	:	standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves
on the task being performed and the risks involved and should be approved by a specialist before handling this product.	Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be

<u>One</u>

## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1		Page 9 of 22
Revision Date 08/30/2019		Print Date 09/03/2019
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

#### **Appearance**

Physical state	:	liquid [liquid]
Color	:	TAN
Odor	:	Not available.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
(flammable) limits Vapor pressure	:	<b>Upper:</b> Not available. Not available.
	:	
Vapor pressure	:	Not available.
Vapor pressure Vapor density	:	Not available. Not available.
Vapor pressure Vapor density Relative density	::	Not available. Not available. Not available.
Vapor pressure Vapor density Relative density Solubility	:::::::::::::::::::::::::::::::::::::::	Not available. Not available. Not available. Not available.
Vapor pressure Vapor density Relative density Solubility Solubility in water	:::::::::::::::::::::::::::::::::::::::	Not available. Not available. Not available. Not available. Not available.
Vapor pressure Vapor density Relative density Solubility Solubility in water Partition coefficient: n-	: : : : : : : : : : : : : : : : : : : :	Not available. Not available. Not available. Not available. Not available.
Vapor pressure Vapor density Relative density Solubility Solubility in water Partition coefficient: n- octanol/water	:	Not available. Not available. Not available. Not available. Not available. Not available.
Vapor pressure Vapor density Relative density Solubility Solubility in water Partition coefficient: n- octanol/water Auto-ignition temperature	:	Not available. Not available. Not available. Not available. Not available. Not available.
Vapor pressure Vapor density Relative density Solubility Solubility in water Partition coefficient: n- octanol/water Auto-ignition temperature Decomposition temperature	:	Not available. Not available. Not available. Not available. Not available. Not available. Not available. Not available.

## Section 10. Stability and reactivity

:

Reactivity

No specific test data related to reactivity available for this product or its ingredients.



## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019

Page 10 of 22 Print Date 09/03/2019

Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid Incompatible materials	:	Keep away from extreme heat and oxidizing agents. Avoid contact with acetal homopolymers and acetyl homopolymers during processing.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Information on toxicological effects**

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure			
Ethyl benzene							
	LD50 Oral	Rat	3,500 mg/kg	-			
<b>Remarks - Inhalation:</b>	No applicable toxi	No applicable toxicity data					
	LD50 Dermal	Rabbit	5,000 mg/kg	-			
Titanium dioxide							
Remarks - Oral:	No applicable toxi	city data					
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h			
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-			
Xylenes (o-, m-, p- isomers)							
	LD50 Oral	Rat	4,300 mg/kg	-			
	LC50 Inhalation	Rat	5,000 ppm	4 h			
<b>Remarks - Dermal:</b>	No applicable toxi	city data					
Tetrahydrofuran							
	LD50 Oral	Rat	1,650 mg/kg	-			
<b>Remarks - Inhalation:</b>	No applicable toxi	city data					
Remarks - Dermal:	No applicable toxicity data						
Methyl ethyl ketone							
	LD50 Oral	Rat	2,737 mg/kg	-			
<b>Remarks - Inhalation:</b>	No applicable toxicity data						
	LD50 Dermal	Rabbit	6,480 mg/kg	-			
Conclusion/Summary	• Mixtu	re.Not fully tested					

Conclusion/Summary

Mixture.Not fully tested.

#### **Irritation/Corrosion**



## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019 Page 11 of 22 Print Date 09/03/2019

Product/ingredient name	Result	Species	Score	Exposure	Observation
Ethyl benzene	Skin - Mild	Rabbit		24 hrs	-
-	irritant				
	Eyes - Severe	Rabbit			-
	irritant				
Titanium dioxide	Skin - Mild	Human		72 hrs	-
	irritant				
Xylenes (o-, m-, p- isomers)	Skin - Mild	Rat		8 hrs	-
	irritant				
	Skin -	Rabbit			-
	Moderate				
	irritant				
	Skin -	Rabbit		24 hrs	-
	Moderate				
	irritant				
	Eyes - Mild	Rabbit			-
	irritant				
	Eyes - Severe	Rabbit		24 hrs	_
	irritant	- woon			
Methyl ethyl ketone	Skin - Mild	Rabbit		24 hrs	-
	irritant	imoon		21110	
	Skin -	Rabbit		24 hrs	-
	Moderate	Rubble		21115	
	irritant				
	Skin - Mild	Rabbit		24 hrs	-
	irritant	Rubble		24 11 5	
Conclusion/Summary					
Skin	: M	ixture.Not full	v tested.		
Eyes		ixture.Not full			
Respiratory		ixture.Not full			
J			<b>)</b>		
<u>Sensitization</u>					
<b>Conclusion/Summary</b>					
Skin		ixture.Not full			
Respiratory	: M	ixture.Not full	y tested.		
M-4					
<b>Mutagenicity</b>					
Conclusion/Summary	: M	ixture.Not full	v tested.		
			,		
<b>Carcinogenicity</b>					
Conclusion/Summary	: M	ixture.Not full	v tested.		
<u>Classification</u>	• 111		j tostou.		



## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019 Page 12 of 22 Print Date 09/03/2019

Product/ingredientOSnameEthyl benzeneTitanium dioxideXylenes (o-, m-, p-	SHA	IARC     2B	NTP
Ethyl benzene Titanium dioxide			
Titanium dioxide			
		2B	
		3	
isomers)		-	
Tetrahydrofuran		2B	
<u>Reproductive toxicity</u>			
Conclusion/Summary	:	Mixture.Not fu	lly tested.
<u>Teratogenicity</u>			
Conclusion/Summary	:	Mixture.Not fu	lly tested.
Specific target organ toxicity (sin Not available.	ngle exp	osure)	
Specific target organ toxicity (re Not available.	peated (	exposure)	
Aspiration hazard			
Product/ingredient name			Result
Ethyl benzene			ASPIRATION HAZARD - Category 1
Information on likely routes of exposure	:	Not available.	
Potential acute health effects			
Eye contact	:	Causes serious	eve irritation.
Inhalation			ificant effects or critical hazards.
Skin contact	:	Causes skin irr	
Ingestion	:	No known sign	ificant effects or critical hazards.
Symptoms related to the physical	, chemi	cal and toxicolog	gical characteristics
Eye contact	:	Adverse sympt pain or irritatio watering	oms may include the following: n
		redness	
Inhalation	:	No specific dat	a.

12/22

<u>lyOne</u>

## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019 Page 13 of 22 Print Date 09/03/2019

Ingestion	:	redness No specific data.				
Delayed and immediate effects as well as chronic effects from short and long-term exposure						
Short term exposure						
Potential immediate effects Potential delayed effects	:	Not available. Not available.				
Long term exposure						
Potential immediate effects Potential delayed effects	:	Not available. Not available.				
Potential chronic health effects						
Conclusion/Summary	:	Mixture.Not fully tested.				
General Carcinogenicity	:	No known significant effects or critical hazards. Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.				
Mutagenicity Teratogenicity Developmental effects Fertility effects	::	No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards.				

### Numerical measures of toxicity

### Acute toxicity estimates

Route	ATE value
Oral	4,868.4 mg/kg
Route	ATE value
Inhalation (gases)	237,247.9 ppm

## Section 12. Ecological information

### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Ethyl benzene			
	Acute LC50 4.2 Mg/l Fresh water	Fish - Fish	96 h
	13/22		



## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019 Page 14 of 22 Print Date 09/03/2019

Remarks - Acute - Fish:	Acute		
	Acute EC50 6.53 Mg/l Marine	Aquatic invertebrates.	48 h
	water	Crustaceans	
Remarks - Acute - Aquatic	Acute		
invertebrates.:			-
	Acute EC50 2.93 Mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
Remarks - Acute - Aquatic invertebrates.:	Acute		
	Acute EC50 4.6 Mg/l Fresh water	Aquatic plants - Algae	72 h
Remarks - Acute - Aquatic plants:	Acute		
	Acute EC50 3.6 Mg/l Fresh water	Aquatic plants - Algae	96 h
Remarks - Acute - Aquatic plants:	Acute	·	
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic - Aquatic invertebrates.:	No applicable toxicity data		
Titanium dioxide			
	Acute LC50 > 1,000 Mg/l Marine water	Fish - Fish	96 h
Remarks - Acute - Fish:	Acute		
	Acute LC50 3 Mg/l Fresh water	Aquatic invertebrates. Crustaceans	48 h
Remarks - Acute - Aquatic invertebrates.:	Acute		
	Acute LC50 6.5 Mg/l Fresh water	Aquatic invertebrates. Daphnia	48 h
Remarks - Acute - Aquatic invertebrates.:	Acute		
Remarks - Acute - Aquatic plants:	No applicable toxicity data		
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic - Aquatic invertebrates.:	No applicable toxicity data		
Xylenes (o-, m-, p- isomers)			
	Acute LC50 13.4 Mg/l Fresh water	Fish - Fish	96 h
Remarks - Acute - Fish:	Acute		
	Acute LC50 8.5 Mg/l Marine water	Aquatic invertebrates. Crustaceans	48 h
Remarks - Acute - Aquatic	Acute		
invertebrates.:			
Remarks - Acute - Aquatic plants:	No applicable toxicity data		



## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019 Page 15 of 22 Print Date 09/03/2019

Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:			
Tetrahydrofuran			
	Acute LC50 2,160 Mg/l Fresh	Fish - Fish	96 h
	water		
Remarks - Acute - Fish:	Acute		
Remarks - Acute - Aquatic	No applicable toxicity data		
invertebrates.:			
Remarks - Acute - Aquatic	No applicable toxicity data		
plants:			
	Chronic NOEC 367 Mg/l Fresh	Fish - Fish	33 d
	water		
Remarks - Chronic - Fish:	Chronic		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:			
Methyl ethyl ketone	I		•
	Acute LC50 3,220 Mg/l Fresh	Fish - Fish	96 h
	water		
Remarks - Acute - Fish:	Acute		1
	Acute EC50 5.091 Mg/l Fresh	Aquatic invertebrates.	48 h
	water	Daphnia	
<b>Remarks - Acute - Aquatic</b>	Acute		
invertebrates.:		1	
	Acute EC50 > 500 Mg/l Marine	Aquatic plants - Algae	96 h
	water		
Remarks - Acute - Aquatic	Acute		
plants:			
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:	NT / 111		
Conclusion/Summary	: Not available.		

Persistence and degradability

Conclusion/Summary

: Not available.

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Ethyl benzene	3.6	-	low
Xylenes (o-, m-, p- isomers)	3.15	8.10 - 25.90	low



## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019

### Page 16 of 22 Print Date 09/03/2019

Tetrahydrofuran	0.45	-	low
Methyl ethyl ketone	0.29	-	low

#### Mobility in soil

Soil/water partition coefficient	:	Not available.
(KOC)		
Other adverse effects	:	No known significant effects or critical hazards.

:

## Section 13. Disposal considerations

**Disposal methods** 

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

#### United States - RCRA Toxic hazardous waste "U" List: Listed

Ingredient	CAS #	Status	Reference number
Methyl ethyl ketone	78-93-3	Listed	
Tetrahydrofuran	109-99-9	Listed	
Xylenes (o-, m-, p- isomers)	1330-20-7	Listed	

## Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water Proper Shipping Name: Paint

P<u>olyOne</u>

## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019 Page 17 of 22 Print Date 09/03/2019

Technical Name: Hazard Class / Division UN Number Packing Group Label Required	3 UN1263 II 3
International Air ICAO/IATA	Consult mode specific transport rules
International Water IMO/IMDG	Consult mode specific transport rules

## Section 15. Regulatory information

U.S. Federal regulations	<ul> <li>United States - TSCA 12(b) - Chemical export notification: None of the components are listed.</li> <li>United States - TSCA 4(a) - Final Test Rules: Not listed</li> <li>United States - TSCA 4(a) - ITC Priority list: Not listed</li> <li>United States - TSCA 4(a) - Proposed test rules: Not listed</li> <li>United States - TSCA 4(a) - Proposed test rules: Not listed</li> <li>United States - TSCA 4(f) - Priority risk review: Not listed</li> <li>United States - TSCA 5(a)2 - Final significant new use rules: Not listed</li> <li>United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed</li> <li>United States - TSCA 5(e) - Substances consent order: Not listed</li> <li>United States - TSCA 6 - Final risk management: Not listed</li> <li>United States - TSCA 6 - Proposed risk management: Not listed</li> <li>United States - TSCA 8(a) - Chemical risk rules: Not listed</li> <li>United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined</li> <li>United States - TSCA 8(a) - Preliminary assessment report</li> <li>(PAIR): Listed Tetrahydrofuran</li> </ul>
	<ul> <li>United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed</li> <li>United States - TSCA 8(d) - Health and safety studies: Not listed</li> <li>United States - EPA Clean water act (CWA) section 307 - Priority</li> <li>pollutants: Listed Benzene, methyl- Ethyl benzene</li> <li>United States - EPA Clean water act (CWA) section 311 - Hazardous substances: Listed</li> </ul>

ne

## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019 Page 18 of 22 Print Date 09/03/2019

United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed

Clean Air Act Section 112(b)	:	Listed
Hazardous Air Pollutants (HAPs) Clean Air Act Section 602 Class I	:	Not listed
Substances Clean Air Act Section 602 Class II	:	Not listed
Substances DEA List I Chemicals (Precursor	:	Not listed
Chemicals) DEA List II Chemicals (Essential	•	Listed
Chemicals)	•	Listu

#### US. EPA CERCLA Hazardous Substances (40 CFR 302)

:

Chemical Name	CAS-No.	RQ for component
Tetrahydrofuran	109-99-9	1,000 lb(s) 454 kg
Methyl ethyl ketone	78-93-3	5,000 lb(s) 2,270 kg 2,270 kg 5,000 lb(s)

### SARA 311/312

Classification

SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2

### **Composition/information on ingredients**

Name	%	Classification
Methyl ethyl ketone	>= 25 - <= 50	FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A
Tetrahydrofuran	>= 5 - <= 10	FLAMMABLE LIQUIDS - Category 2



## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019 Page 19 of 22 Print Date 09/03/2019

		ACUTE TOXICITY - oral - Category 4 CARCINOGENICITY - Category 2
Ethyl benzene	> 0 - <= 0.3	FLAMMABLE LIQUIDS - Category 3 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2 ASPIRATION HAZARD - Category 1
Xylenes (o-, m-, p- isomers)	>= 1 - <= 3	FLAMMABLE LIQUIDS - Category 2 ACUTE TOXICITY - inhalation - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A
Titanium dioxide	>= 1 - <= 3	CARCINOGENICITY - Category 2

### SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 3
	Ethyl benzene	100-41-4	0 - 0.3
Supplier notification         Xylenes (o-, m-, p- isomers)		1330-20-7	1 - 3
	Ethyl benzene	100-41-4	0 - 0.3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations	
Massachusetts	None of the components are listed.
New York	: The following components are listed:
	Methyl ethyl ketone
	Tetrahydrofuran
	Xylenes (o-, m-, p- isomers)
	Ethyl benzene
New Jersey	: The following components are listed:
-	Xylenes (o-, m-, p- isomers)
	Titanium dioxide
	Isopropanol
	Ethyl benzene
	Methyl ethyl ketone
	Tetrahydrofuran
	40/00

ne

## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019 Page 20 of 22 Print Date 09/03/2019

Pennsylvania

: The following components are listed: Methyl ethyl ketone

Tetrahydrofuran

Ethyl benzene

Isopropanol

Titanium dioxide

Xylenes (o-, m-, p- isomers)

Silica gel

### California Prop. 65

**WARNING:** This product can expose you to chemicals including Ethyl benzene, Titanium dioxide, which are known to the State of California to cause cancer, and Benzene, methyl-, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Ethyl benzene	No.	No.
Benzene, methyl-	No.	No.
Titanium dioxide	No.	No.

United States inventory (TSCA 8b)	:	All components are listed or exempted.
Canada inventory	:	All components are listed or exempted.
International regulations		
<u>Inventory list</u>		
Australia	:	Not determined.
Canada	:	All components are listed or exempted.
China	:	Not determined.
Europe inventory	:	Not determined.
Japan	:	Not determined.
New Zealand	:	Not determined.
Philippines	:	Not determined.
Republic of Korea	:	Not determined.
Taiwan	:	Not determined.
Turkey	:	Not determined.
United States	:	All components are listed or exempted.
		20/22

## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019 Page 21 of 22 Print Date 09/03/2019

## Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

<u>History</u>		
Date of printing	:	09/03/2019
Date of issue/Date of revision	:	08/30/2019
Date of previous issue	:	11/07/2018
Version	:	1.1
Key to abbreviations	:	ATE = Acute Toxicity Estimate
•		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From
		Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)
		UN = United Nations
References		Not available.
Netel chices	•	not available.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other



## 2530-HH SAND TOUCH-UP PAINT

Version Number 1.1 Revision Date 08/30/2019 Page 22 of 22 Print Date 09/03/2019

materials or in any process, unless specified in the text.