### Geon™ SK236 Charcoal Strand Coating NP

Version Number 1.0 Revision Date 11/28/2018 Page 1 of 18 Print Date 12/06/2018

# SAFETY DATA SHEET

#### Geon<sup>™</sup> SK236 Charcoal Strand Coating NP

Section 1. Identification		
GHS product identifier	:	Geon <sup>™</sup> SK236 Charcoal Strand Coating NP
Chemical name	:	Mixture
CAS number	:	Mixture
Other means of identification	:	FO20043381
Product type	:	liquid
Delevent identified uses of the sub-	tono	e or mixture and uses advised against
Product use	:	Industrial applications. Plastics.
Supplier's details	:	POLYONE CORPORATION
		33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

### Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2

#### **GHS** label elements



## Geon™ SK236 Charcoal Strand Coating NP

Version Number 1.0	Page 2 of 18
Revision Date 11/28/2018	Print Date 12/06/2018

Hazard pictograms	:	
Signal word Hazard statements	:	Warning May cause an allergic skin reaction. Suspected of causing cancer.
Precautionary statements		
General	:	Not applicable.
Prevention	:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Avoid breathing vapor. Contaminated work clothing must not be allowed out of the workplace.
Response	:	IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention.
Storage	:	Store locked up.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known.

## Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	FO20043381

#### CAS number/other identifiers

Ingredient name	%	CAS number
Antimony trioxide	1 - 3	1309-64-4
Carbon black	0.3 - 1	1333-86-4
Proprietary Hazardous Compounds	0.3 - 1	Not available.
r		



### Geon<sup>™</sup> SK236 Charcoal Strand Coating NP

Version Number 1.0 Revision Date 11/28/2018 Page 3 of 18 Print Date 12/06/2018

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed



## Geon™ SK236 Charcoal Strand Coating NP

Version Number 1.0	Page 4 of 18
Revision Date 11/28/2018	Print Date 12/06/2018

#### Potential acute health effects

Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	May cause an allergic skin reaction.
Ingestion	:	No known significant effects or critical hazards.
Over-exposure signs/symptoms		
Eye contact	:	No specific data.
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness
Ingestion	:	No specific data.
Indication of immediate medical att	<u>entio</u>	n and special treatment needed, if necessary
Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## **Section 5. Firefighting measures**

#### **Extinguishing media**

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or $CO_2$ . None known.
Specific hazards arising from the chemical Hazardous thermal decomposition products	:	In a fire or if heated, a pressure increase will occur and the container may burst. May emit Hydrogen Chloride (HCl). Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides



## Geon™ SK236 Charcoal Strand Coating NP

Version Number 1.0	Page 5 of 18
Revision Date 11/28/2018	Print Date 12/06/2018

Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any
		personal risk or without suitable training.
Special protective equipment for	:	Fire-fighters should wear appropriate protective equipment and self-
fire-fighters		contained breathing apparatus (SCBA) with a full face-piece operated
		in positive pressure mode.

## Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containment	nt ai	nd cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.



## Geon™ SK236 Charcoal Strand Coating NP

Version Number 1.0 Revision Date 11/28/2018 Page 6 of 18 Print Date 12/06/2018

## Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

#### Control parameters

#### **Occupational exposure limits**

Ingredient name	Exposure limits	
Carbon black	OSHA PEL 1989 (1989-03-01) TWA 3.5 mg/m3 OSHA PEL (1993-06-30)	



## Geon™ SK236 Charcoal Strand Coating NP

Version Number 1.0 Revision Date 11/28/2018 Page 7 of 18 Print Date 12/06/2018

		TWA 3.5 mg/m3 <b>NIOSH REL (1994-06-01)</b> TWA 3.5 mg/m3 TWA 0.1 mgPAH/m <sup>3</sup> <b>ACGIH TLV (2010-12-06)</b> TWA 3 mg/m3 Form: Inhalable fraction
Proprietary Hazardous Compounds		None.
Antimony trioxide		OSHA PEL (1993-06-30) TWA 0.5 mg/m3 (as antimony) NIOSH REL (1994-06-01) TWA 0.5 mg/m3 (as antimony) OSHA PEL 1989 (1989-03-01) TWA 0.5 mg/m3 (as antimony)
Appropriate engineering controls Environmental exposure controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures Eye/face protection	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the 7/18

7/18



## Geon™ SK236 Charcoal Strand Coating NP

Version Number 1.0	Page 8 of 18
Revision Date 11/28/2018	Print Date 12/06/2018

	parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

#### **Appearance**

Physical state Color	:	liquid [liquid] BLACK
Odor		Not available.
Odor threshold	:	Not available.
рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n-	:	Not available.
octanol/water		
Auto-ignition temperature	:	Not available.
<b>Decomposition temperature</b>	:	Not available.



### Geon™ SK236 Charcoal Strand Coating NP

Version Number 1.0 Revision Date 11/28/2018 Page 9 of 18 Print Date 12/06/2018

SADT	: Not available.	
Viscosity	<b>: Dynamic:</b> Not available.	
	Kinematic: Not available	<b>e</b> .

## Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Avoid contact with acetal homopolymers and acetyl homopolymers during processing.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure		
Carbon black						
	LD50 Oral	Rat	15,400 mg/kg	-		
<b>Remarks - Inhalation:</b>	No applicable to	oxicity data				
Remarks - Dermal:	No applicable to	oxicity data				
Proprietary Hazardous Compo	unds					
Remarks - Oral:	No applicable to	No applicable toxicity data				
<b>Remarks - Inhalation:</b>	No applicable toxicity data					
Remarks - Dermal:	No applicable toxicity data					
Antimony trioxide						
	LD50 Oral	Rat	34,000 mg/kg	-		
<b>Remarks - Inhalation:</b>	No applicable toxicity data					
Remarks - Dermal:	No applicable toxicity data					
Conclusion/Summary	• Mi	vture Not fully teste	h			

Conclusion/Summary

Mixture.Not fully tested.

#### Irritation/Corrosion



## Geon™ SK236 Charcoal Strand Coating NP

Version Number 1.0 Revision Date 11/28/2018 Page 10 of 18 Print Date 12/06/2018

Product/ingredient name	Result	Species	Score	Exposure	Observation
Antimony trioxide	Eyes - Mild irritant	Rabbit			-
Conclusion/Summann	irritant				
Conclusion/Summary Skin		lixture.Not fu	lly tostad		
Skin Eyes		lixture.Not fu			
Respiratory		lixture.Not fu			
Kespii ator y	• IV	lixture.not iu	ny testeu.		
<b>Sensitization</b>					
Conclusion/Summary					
Skin	: N	lixture.Not fu	lly tested.		
Respiratory	: N	lixture.Not fu	lly tested.		
			•		
<b>Mutagenicity</b>					
Conclusion/Summary	: N	lixture.Not fu	lly tested.		
<b>Carcinogenicity</b>					
Conclusion/Summary	: N	lixture.Not fu	llv tested.		
Classification	•				
Product/ingredient	OSHA	IARC	NTP		
name					
Carbon black		2B			
Antimony trioxide		2B			
Tintinony trontae		20			
<b><u>Reproductive toxicity</u></b>					
Conclusion/Summary	: N	lixture.Not fu	lly tested.		
<b>Teratogenicity</b>					
Conclusion/Summary	: N	lixture.Not fu	lly tested.		
Specific target organ toxici	ty (single exposu	re)			
Not available.	<u>, (*<u>B</u>-0</u> p -== -				
Specific target organ toxici	ty (repeated exp	<u>osure)</u>			
Not available.					
Aspiration hazard					
Not available.					
rtot available.					



## Geon™ SK236 Charcoal Strand Coating NP

Version Number 1.0 Revision Date 11/28/2018 Page 11 of 18 Print Date 12/06/2018

Information on likely routes of exposure	:	Not available.	
Potential acute health effects			
Eye contact Inhalation Skin contact Ingestion	:	No known significant effects or critical hazards. No known significant effects or critical hazards. May cause an allergic skin reaction. No known significant effects or critical hazards.	
Symptoms related to the physical, ch	emic	al and toxicological characteristics	
Eye contact Inhalation Skin contact	::	No specific data. No specific data. Adverse symptoms may include the following: irritation redness	
Ingestion	:	No specific data.	
Delayed and immediate effects as we	ll as	chronic effects from short and long-term exposure	
<u>Short term exposure</u>			
Potential immediate effects Potential delayed effects	:	Not available. Not available.	
Long term exposure			
Potential immediate effects Potential delayed effects	:	Not available. Not available.	
Potential chronic health effects			
Conclusion/Summary	:	Mixture.Not fully tested.	
General	:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.	
Carcinogenicity	:	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.	
Mutagenicity Teratogenicity Developmental effects Fertility effects	::	No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards.	

Numerical measures of toxicity



## Geon™ SK236 Charcoal Strand Coating NP

Version Number 1.0 Revision Date 11/28/2018 Page 12 of 18 Print Date 12/06/2018

#### Acute toxicity estimates

Not available.

## Section 12. Ecological information

**Toxicity** 

Product/ingredient name	Result	Species	Exposure		
Carbon black					
Remarks - Acute - Fish:	No applicable toxicity data				
	Acute EC50 37.563 Mg/l Fresh	Aquatic invertebrates.	48 h		
	water	Daphnia			
Remarks - Acute - Aquatic	Acute				
invertebrates.:					
Remarks - Acute - Aquatic	No applicable toxicity data				
plants:					
Remarks - Chronic - Fish:	No applicable toxicity data				
<b>Remarks - Chronic -</b>	No applicable toxicity data				
Aquatic invertebrates.:					
Proprietary Hazardous Compo					
Remarks - Acute - Fish:	No applicable toxicity data				
Remarks - Acute - Aquatic	No applicable toxicity data				
invertebrates.:					
Remarks - Acute - Aquatic	No applicable toxicity data				
plants:					
Remarks - Chronic - Fish:	No applicable toxicity data				
<b>Remarks - Chronic -</b>	No applicable toxicity data				
Aquatic invertebrates.:					
Antimony trioxide					
	Acute LC50 > 530 Mg/l Fresh	Fish - Fish	96 h		
	water				
Remarks - Acute - Fish:	Acute	1			
	Acute EC50 560 Mg/l Fresh water	Aquatic invertebrates.	48 h		
		Crustaceans			
Remarks - Acute - Aquatic	Acute				
invertebrates.:			40.1		
	Acute EC50 0.42345 Mg/l Fresh	Aquatic invertebrates.	48 h		
	water	Daphnia			
Remarks - Acute - Aquatic	Acute				
invertebrates.:	A puto EC50 0 72 Mg/l Eroch	Aquatia planta Alasa	70 h		
	Acute EC50 0.73 Mg/l Fresh water	Aquatic plants - Algae	72 h		
	12/18				



### Geon™ SK236 Charcoal Strand Coating NP

Version Number 1.0 Revision Date 11/28/2018 Page 13 of 18 Print Date 12/06/2018

Remarks - Acute - Aquatic	Acute
plants:	· · · · · · · · · · · · · · · · · · ·
	Acute EC50 0.74 Mg/l Fresh water Aquatic plants - Algae 96 h
Remarks - Acute - Aquatic	Acute
plants:	
	Acute NOEC 0.2 Mg/l Fresh water Aquatic plants - Algae 96 h
Remarks - Acute - Aquatic	Chronic
plants:	
Remarks - Chronic - Fish:	No applicable toxicity data
Remarks - Chronic -	No applicable toxicity data
Aquatic invertebrates.:	
Conclusion/Summary	: Not available.
<u>Persistence and degradability</u> Conclusion/Summary <u>Bioaccumulative potential</u>	: Not available.
Not available. <u>Mobility in soil</u>	
Soil/water partition coefficie (KOC)	ent : Not available.
Other adverse effects	: No known significant effects or critical hazards.
Section 13. Dispos	al considerations

**Disposal methods** The generation of waste should be avoided or minimized wherever : possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains



### Geon™ SK236 Charcoal Strand Coating NP

Version Number 1.0 Revision Date 11/28/2018 Page 14 of 18 Print Date 12/06/2018

and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

## Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	:	Not regulated for transportation.
International Air ICAO/IATA	:	Consult mode specific transport rules
International Water IMO/IMDG	:	Consult mode specific transport rules

## Section 15. Regulatory information

U.S. Federal regulations	:	<ul> <li>United States - TSCA 12(b) - Chemical export notification: None of the components are listed.</li> <li>United States - TSCA 4(a) - Final Test Rules: Not listed</li> <li>United States - TSCA 4(a) - ITC Priority list: Not listed</li> <li>United States - TSCA 4(a) - Proposed test rules: Not listed</li> <li>United States - TSCA 4(f) - Priority risk review: Not listed</li> <li>United States - TSCA 5(a)2 - Final significant new use rules:</li> <li>Listed 4-Nonylphenol, branched</li> </ul>
		United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Listed Lead
		United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined United States - TSCA 8(a) - Preliminary assessment report (PAIR): Listed 4-Nonylphenol, branched Acetaldehyde



### Geon™ SK236 Charcoal Strand Coating NP

Version Number 1.0	Page 15 of 18
Revision Date 11/28/2018	Print Date 12/06/2018

		United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Arsenic Lead Vinyl chloride monomer Phenol 2-Ethylhexanoic acid zinc salt Zinc sulfide Antimony trioxide United States - EPA Clean water act (CWA) section 311 - Hazardous substances: Listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed
Clean Air Act Section 112(b)	:	Listed
Hazardous Air Pollutants (HAPs) Clean Air Act Section 602 Class I Substances	:	Not listed
Clean Air Act Section 602 Class II	:	Not listed
Substances DEA List I Chemicals (Precursor Chemicals)	:	Not listed
DEA List II Chemicals (Essential Chemicals)	:	Not listed

#### US. EPA CERCLA Hazardous Substances (40 CFR 302)

:

not applicable

#### SARA 311/312

Classification

SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2

#### **Composition/information on ingredients**

#### <u>SARA 313</u>



### Geon<sup>™</sup> SK236 Charcoal Strand Coating NP

Version Number 1.0 Revision Date 11/28/2018 Page 16 of 18 Print Date 12/06/2018

	Product name	CAS number	%
Form R - Reporting Antimony trioxid requirements		1309-64-4	1 - 3
	Lead	7439-92-1	0 - 0.1
Supplier notification	Lead	7439-92-1	0 - 0.1
	Antimony trioxide	1309-64-4	1 - 3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations	
Massachusetts	: None of the components are listed.
New York	: The following components are listed: Antimony trioxide
New Jersey	: The following components are listed: Ethene, chloro-, homopolymer Antimony trioxide Carbon black
Pennsylvania	: The following components are listed: Antimony trioxide
	Carbon black

#### California Prop. 65

**WARNING:** This product can expose you to chemicals including Antimony trioxide, Carbon black, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Carbon black	No.	No.
Antimony trioxide	No.	No.

#### United States inventory (TSCA 8b) : All components are listed or exempted.

**Canada inventory** 

All components are listed of exempted.

ry : All c

All components are listed or exempted.

#### **International regulations**

#### **Inventory list**



### Geon™ SK236 Charcoal Strand Coating NP

Version Number 1.0 Revision Date 11/28/2018 Page 17 of 18 Print Date 12/06/2018

Australia		Not determined.
Canada	:	All components are listed or exempted.
China	:	Not determined.
Europe inventory	:	Not determined.
Japan	:	Not determined.
New Zealand	:	Not determined.
Philippines	:	Not determined.
Republic of Korea	:	Not determined.
Taiwan	:	Not determined.
Turkey	:	Not determined.
United States	:	All components are listed or exempted.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

<u>Instory</u>		
Date of printing	:	12/06/2018
Date of issue/Date of revision	:	11/28/2018
Date of previous issue	:	00/00/0000
Version	:	1.0
Key to abbreviations	:	ATE = Acute Toxicity Estimate
·		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From
		Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)



### Geon™ SK236 Charcoal Strand Coating NP

:

Version Number 1.0 Revision Date 11/28/2018 Page 18 of 18 Print Date 12/06/2018

References

UN = United Nations Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.