

CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Page 1 of 21 Revision Date 03/06/2024 Print Date 03/07/2024

SAFETY DATA SHEET

CORETM SK292 (PUROLATOR UM524000)

Section 1. Identification

GHS product identifier : CORE™ SK292 (PUROLATOR UM524000)

Chemical name: MixtureCAS number: MixtureOther means of identification: FO20048664Product type: liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : AVIENT CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (844) 4AVIENT

Emergency telephone number (with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Classification of the substance or

mixture

SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A

GHS label elements



CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Page 2 of 21 Revision Date 03/06/2024 Print Date 03/07/2024

Hazard pictograms

Signal word : Danger

Hazard statements : Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye damage.

May cause cancer.

Precautionary statements

: Not applicable.

Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing must

not be allowed out of the workplace.

Response: IF exposed or concerned: Get medical advice or attention. Take off

contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor.

Storage : Store locked up.

Disposal : Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Supplemental label elements : None known.

Hazards not otherwise classified : None known.

Not available.

Section 3. Composition/information on ingredients

Substance/mixture:MixtureChemical name:MixtureOther means of identification:FO20048664

CAS number/other identifiers

Ingredient name	%	CAS number
Distillates (petroleum), light catalytic cracked	>= 25 - <= 50	64741-59-9



CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Page 3 of 21 Revision Date 03/06/2024 Print Date 03/07/2024

Calcium oxide	>= 5 - <= 10	1305-78-8
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	>= 5 - <= 10	68515-48-0
1,2-benzanthracene	> 0 - <= 0.3	56-55-3
Benzo[a]pyrene	> 0 - <= 0.3	50-32-8
Chrysene	> 0 - <= 0.3	218-01-9
Quartz	> 0 - <= 0.3	14808-60-7
Diphenyloxide-4,4'-disulfohydrazide	> 0 - <= 0.3	80-51-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Get medical attention immediately. Call a poison center or physicia Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.	ne
Inhalation	: Get medical attention immediately. Call a poison center or physicial Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the resc should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open	ole uer
Skin contact	 airway. Loosen tight clothing such as a collar, tie, belt or waistband Get medical attention immediately. Call a poison center or physicia Wash with plenty of soap and water. Remove contaminated clothin and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minut Chemical burns must be treated promptly by a physician. In the even 	an. ng ore tes.
	2/24	



CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Revision Date 03/06/2024 Page 4 of 21 Print Date 03/07/2024

of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion : Get medical attention immediately. Call a poison center or physician.

Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen

tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact: Causes skin irritation. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without

suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give

4/21



CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Revision Date 03/06/2024 Page 5 of 21 Print Date 03/07/2024

mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media In case of fire, use water spray (fog), foam, dry chemical or CO₂.

None known.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

In a fire or if heated, a pressure increase will occur and the container

may burst.

May emit Hydrogen Chloride (HCl).

Decomposition products may include the following materials:

carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides

Special protective actions for firefighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

5/21



CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Revision Date 03/06/2024 Page 6 of 21 Print Date 03/07/2024

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with

water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal

contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach

release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency

contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures: Put on appropriate personal protective equipment (see Section 8).

Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse

container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See

also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must



CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Revision Date 03/06/2024 Page 7 of 21 Print Date 03/07/2024

be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

OSH REL (1994-06-01) VA 2 mg/m3 SHA PEL 1989 (1989-03-01) VA 5 mg/m3 SHA PEL (1993-06-30) VA 5 mg/m3
VA 2 mg/m3 SHA PEL 1989 (1989-03-01) VA 5 mg/m3 SHA PEL (1993-06-30)
ne.
OSH REL (2010-09-01) VA 0.1 mg/m3 SHA PEL 1989 (1989-03-01) VA 0.2 mg/m3 Form: BEN_SOL SHA PEL (1993-06-30) VA 0.2 mg/m3 Form: BEN_SOL
OSH REL (2010-09-01) VA 0.1 mg/m3 SHA PEL 1989 (1989-03-01) VA 0.2 mg/m3 Form: BEN_SOL SHA PEL (1993-06-30) VA 0.2 mg/m3 Form: BEN_SOL
SHA PEL (1993-06-30) VA 0.2 mg/m3 Form: BEN_SOL OSH REL (2010-09-01) VA 0.1 mg/m3 SHA PEL 1989 (1989-03-01) VA 0.2 mg/m3 Form: BEN_SOL



CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Revision Date 03/06/2024 Page 8 of 21 Print Date 03/07/2024

Quartz	OSHA PEL 1989 (1989-03-01) TWA 0.1 mg/m3 (Calculated as Quartz) Form: Respirable dust OSHA PEL Z3 (1997-09-03) TWA 250 MPPCF / (%SiO2+5) Form: Respirable TWA 10 MG /M3 / (%SiO2+2) Form: Respirable OSHA PEL Z3 (1997-09-03) TWA 30 MG /M3 / (%SiO2+2) Form: Total dust NIOSH REL (1994-06-01) TWA 0.05 mg/m3 Form: Respirable dust ACGIH TLV (2005-12-09) TWA 0.025 mg/m3 Form: Respirable fraction OSHA PEL (2016-06-23) TWA 0.05 mg/m3 Form: Respirable dust
Diphenyloxide-4,4'-disulfohydrazide	None.

Appropriate engineering controls

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.



CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Revision Date 03/06/2024 Page 9 of 21 Print Date 03/07/2024

Skin protection

Hand protection: Chemical-resistant, impervious gloves complying with an approved

standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves

cannot be accurately estimated.

Body protection: Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that

meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state : liquid [liquid]
Color : NOT APPLICABLE

Odor Not available. **Odor threshold** Not available. pН Not available. **Melting point** Not available. **Boiling point** Not available. Flash point Not available. **Burning time** Not available. **Burning rate** Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available.

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressure: Not available.Vapor density: Not available.Relative density: Not available.Solubility: Not available.Solubility in water: Not available.





CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Page 10 of 21 Revision Date 03/06/2024 Print Date 03/07/2024

Partition coefficient: n- : Not applicable.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

Aerosol product

Heat of combustion : Not available.

Ignition distance : Not available. **Enclosed space ignition - Time** : Not available.

equivalent

Enclosed space ignition - : Not available.

Deflagration density

Flame height : Not available. Flame duration : Not available.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur

Conditions to avoid : Keep away from extreme heat and oxidizing agents.

Incompatible materials : Avoid contact with acetal homopolymers and acetyl homopolymers

during processing.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure	
Distillates (petroleum), light catalytic cracked					
	LD50 Oral	Rat	3,200 mg/kg	-	
	LC50 Inhalation	Rat	3.4 Mg/l	4 h	
	Dusts and mists				
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich					



CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Page 11 of 21 Revision Date 03/06/2024 Print Date 03/07/2024

	LD50 Oral	Rat	10,000 mg/kg	-	
Benzenesulfonic acid, 4,4'-oxybis-, 1,1'-dihydrazide					
	LD50 Oral	Rat	2,300 mg/kg	-	

Conclusion/Summary: Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Distillates (petroleum), light catalytic cracked	Skin - Severe irritant	Rabbit	-		-
	Skin - Severe irritant	Rabbit	-		-
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	Eyes - Mild irritant	Rabbit	-		-
Benzo[a]pyrene	Skin - Mild irritant	Mouse	-		-

Conclusion/Summary

Skin:Mixture.Not fully tested.Eyes:Mixture.Not fully tested.Respiratory:Mixture.Not fully tested.

Sensitization

Conclusion/Summary

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

Mutagenicity

Conclusion/Summary: Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
Benz[a]anthracene	-	2B	Reasonably anticipated to be a human carcinogen.
Benzo[a]pyrene	-	1	Reasonably anticipated to be a human carcinogen.
Chrysene	-	2B	-
Ouartz (SiO2)	-	1	Known to be a human carcinogen.

Reproductive toxicity



CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Page 12 of 21 Print Date 03/07/2024 Revision Date 03/06/2024

Conclusion/Summary Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Calcium oxide	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Quartz (SiO2)	Category 1	=	-

Aspiration hazard

Not available.

Information on the likely routes of:

exposure

Not available.

Potential acute health effects

Eve contact Causes serious eye damage.

Inhalation No known significant effects or critical hazards.

Causes skin irritation. May cause an allergic skin reaction. Skin contact

Ingestion No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Adverse symptoms may include the following: pain, watering, redness Eye contact

Inhalation No specific data.

Skin contact Adverse symptoms may include the following: pain or irritation,

redness, blistering may occur

Adverse symptoms may include the following: stomach pains **Ingestion**

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects Not available. **Potential delayed effects** Not available.

Long term exposure



CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Page 13 of 21 Revision Date 03/06/2024 Print Date 03/07/2024

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary: Mixture.Not fully tested.

General : Once sensitized, a severe allergic reaction may occur when

subsequently exposed to very low levels.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards. No known significant

effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
CORE™ SK292 (PUROLATOR UM524000)	12764.7 mg/kg	N/A	N/A	N/A	13.6 Mg/l
Distillates (petroleum), light catalytic cracked	3200 mg/kg	N/A	N/A	N/A	3.4 Mg/l
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	10000 mg/kg	N/A	N/A	N/A	N/A
Benzenesulfonic acid, 4,4'-oxybis-, 1,1'-dihydrazide	500 mg/kg	N/A	N/A	N/A	N/A

Other information: This mixture has not been evaluated as a whole for health effects.

Exposure effects listed are based on existing health data for the

individual components which comprise the mixture.

Section 12. Ecological information



CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Revision Date 03/06/2024 Page 14 of 21 Print Date 03/07/2024

Toxicity

Product/ingredient name	Result	Species	Exposure
Calcium oxide			
	Chronic NOEC 100 Mg/l Fresh	Fish - Oreochromis niloticus	46 d
	water		
Benz[a]anthracene			
	Acute LC50 0.000098 Mg/l	Daphnia - Daphnia magna	48 h
	Fresh water		
Benzo[a]pyrene	•		
	Acute LC50 11 Mg/l Marine	Crustaceans - Gammarus	48 h
	water	duebeni	
	Acute LC50 0.25 Mg/l Fresh	Daphnia - Daphnia magna	48 h
	water		
	Acute EC50 0.005 Mg/l Fresh	Algae - Scenedesmus acutus	72 h
	water		
	Chronic NOEC 0.012 Mg/l Fresh	Crustaceans - Eurytemora	21 d
	water	affinis	

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Calcium oxide	-	2.34	low
1,2-Benzenedicarboxylic acid, di-C8-	8.8	3.00	low
10-branched alkyl esters, C9-rich			
Benz[a]anthracene	5.76	257.04	low
Benzo[a]pyrene	6.13	-	high
Chrysene	5.81	-	high
Benzenesulfonic acid, 4,4'-oxybis-,	-	3.00	low
1,1'-dihydrazide			

Mobility in soil

Soil/water partition coefficient

(KOC)

Not available.

Other adverse effects : No known significant effects or critical hazards.



CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Page 15 of 21 Revision Date 03/06/2024 Print Date 03/07/2024

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water : Not regulated for transportation.

International Air ICAO/IATA

: Consult mode specific transport rules

International Water

IMO/IMDG

: Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations : United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Listed 1,2-

Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich

United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed



CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Revision Date 03/06/2024 Page 16 of 21 Print Date 03/07/2024

United States - TSCA 4(f) - Priority risk review: Not listed

United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed

United States - TSCA 6 - Final risk management: Not listed

United States - TSCA 6 - Proposed risk management: Not listed

United States - TSCA 8(a) - Chemical risk rules: Not listed

United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed

United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not

determined

United States - TSCA 8(a) - Preliminary assessment report

(PAIR): Listed Diphenyloxide-4,4'-disulfohydrazide

Naphthalene

Acetaldehyde

United States - TSCA 8(c) - Significant adverse reaction (SAR):

Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed

United States - EPA Clean water act (CWA) section 307 - Priority

pollutants: Listed 1,2-benzanthracene

Anthracene

Benzo[a]pyrene

Chrysene

9H-Fluorene

Pvrene

Phenanthrene

Naphthalene

benz[e]acephenanthrylene

benzo[k]fluoranthene

Dibenz[a,h]anthracene

Naphthalene, 2-methyl-

Fluoranthene

Zinc

Vinyl chloride monomer

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

United States - Department of commerce - Precursor chemical:

Not listed

Clean Air Act Section 112(b) : Listed



CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Page 17 of 21 Revision Date 03/06/2024 Print Date 03/07/2024

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I : Not listed

Substances

Clean Air Act Section 602 Class II : Not listed

Substances

DEA List I Chemicals (Precursor: Not listed

Chemicals)

DEA List II Chemicals (Essential: Not listed

Chemicals)

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component
Benzo[a]pyrene	50-32-8	1 lb(s)
		0.454 kg
benz[e]acephenanthrylene	205-99-2	1 lb(s)
		0.454 kg

SARA 311/312

Classification : SKIN IRRITATION - Category 2

SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A

Composition/information on ingredients

Name	%	Classification
Distillates (petroleum), light	>= 25 - <= 50	FLAMMABLE LIQUIDS - Category 4
catalytic cracked		ACUTE TOXICITY - inhalation - Category 4
		SKIN IRRITATION - Category 2
		EYE IRRITATION - Category 2A
Calcium oxide	>= 5 - <= 10	SKIN IRRITATION - Category 2
		SERIOUS EYE DAMAGE - Category 1
		SPECIFIC TARGET ORGAN TOXICITY (SINGLE
		EXPOSURE) - Respiratory tract irritation - Category 3
1,2-Benzenedicarboxylic	>= 5 - <= 10	EYE IRRITATION - Category 2B
acid, di-C8-10-branched		
alkyl esters, C9-rich		
Benz[a]anthracene	> 0 - <= 0.3	CARCINOGENICITY - Category 2



CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Revision Date 03/06/2024 Page 18 of 21 Print Date 03/07/2024

Benzo[a]pyrene	> 0 - <= 0.3	CARCINOGENICITY - Category 1A
Chrysene	> 0 - <= 0.3	CARCINOGENICITY - Category 2
Quartz (SiO2)	> 0 - <= 0.3	CARCINOGENICITY - inhalation - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
Benzenesulfonic acid, 4,4'- oxybis-, 1,1'-dihydrazide	> 0 - <= 0.3	COMBUSTIBLE DUSTS ACUTE TOXICITY - oral - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 GERM CELL MUTAGENICITY - Category 2

SARA 313

Form R - Reporting requirements

Product name	CAS number	%
1,2-benzanthracene	56-55-3	>= 0.1 - < 1
Benzo[a]pyrene	50-32-8	>= 0.1 - < 1
Chrysene	218-01-9	>= 0.1 - < 1
benz[e]acephenanthrylene	205-99-2	>= 0 - < 0.1
benzo[k]fluoranthene	207-08-9	>= 0 - < 0.1
Dibenz[a,h]anthracene	53-70-3	>= 0 - < 0.1
Fluoranthene	206-44-0	>= 0 - < 0.1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed:

Calcium carbonate Calcium oxide

Sodium sulfate (solution)



CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Page 19 of 21 Revision Date 03/06/2024 Print Date 03/07/2024

New York : None of the components are listed.
New Jersey : The following components are listed:

Ethene, chloro-, homopolymer

Calcium carbonate Calcium oxide 1,2-benzanthracene Benzo[a]pyrene

Quartz

Pennsylvania: The following components are listed:

Calcium carbonate

Calcium oxide

Sodium sulfate (solution)

California Prop. 65

WARNING: This product can expose you to chemicals including 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich, which are known to the State of California to cause cancer, and Diisodecyl phthalate (mixed isomers), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
1,2-Benzenedicarboxylic acid, di-C8-10- branched alkyl esters, C9-rich	Yes.	-
1,2-benzanthracene	Yes.	-
Anthracene	-	-
Benzo[a]pyrene	Yes.	-
Pyrene	-	-
Quartz	-	-
Phenanthrene	-	-
Diisodecyl phthalate (mixed isomers)	-	Yes.

United States inventory (TSCA 8b) : Not determined.

Canada inventory : Not determined.

International regulations

Inventory list

Australia: Not determined.Canada: Not determined.China: Not determined.

Eurasian Economic Union : Russian Federation inventory: Not determined. **Japan inventory (CSCL):** Not determined.

Japan inventory (ISHL): Not determined.



CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Page 20 of 21 Revision Date 03/06/2024 Print Date 03/07/2024

New Zealand Not determined. **Philippines** Not determined. Republic of Korea Not determined. **Taiwan** Not determined. **Thailand** Not determined. Turkey Not determined. **United States** Not determined. Viet Nam Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	3
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

Date of printing: 03/07/2024Date of issue/Date of revision: 03/06/2024Date of previous issue: 10/27/2021

Version : 1.1

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

References : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-



CORE™ SK292 (PUROLATOR UM524000)

Version Number 1.1 Revision Date 03/06/2024 Page 21 of 21 Print Date 03/07/2024

named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.