

CORE™ SELF ADHERING PLASTISOL QPB-LA93 I

Version Number 1.0 Revision Date 12/16/2021 Page 1 of 19 Print Date 12/17/2021

SAFETY DATA SHEET

CORE™ SELF ADHERING PLASTISOL QPB-LA93 I

Section 1. Identificati	on	
GHS product identifier	:	CORE™ SELF ADHERING PLASTISOL QPB-LA93 I
Chemical name	:	Mixture
CAS number	:	Mixture
Other means of identification	:	FO20048788
Product type	:	liquid
	stance	e or mixture and uses advised against
Product use	:	Industrial applications. Plastics.
Supplier's details	:	AVIENT CORPORATION 33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (844) 4AVIENT
Emergency telephone number (with hours of operation)	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1 CARCINOGENICITY - Category 1A

GHS label elements



CORE™ SELF ADHERING PLASTISOL QPB-LA93 I

Version Numbe	er 1.0
Revision Date	12/16/2021

	Pa	age	2 of	19
Print	Date	12/2	17/20)21

Hazard pictograms	:	
Signal word Hazard statements	:	Danger Causes skin irritation. Causes serious eye damage. May cause cancer.
Precautionary statements		
Prevention	:	Not applicable. Obtain special instructions before use. Wear protective gloves. Wear protective clothing. Wear eye or face protection. Wash thoroughly after handling.
Response	:	Immediately call a POISON CENTER or doctor. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known. Not available.

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	FO20048788

CAS number/other identifiers

Ingredient name	%	CAS number
Calcium oxide	>= 10 - < 20	1305-78-8
Naphtha, petroleum, hydrotreated heavy	>= 1 - <= 3	64742-48-9
Resorcinol	>= 1 - <= 3	108-46-3



CORE™ SELF ADHERING PLASTISOL QPB-LA93 I

Version Number 1.0	
Revision Date 12/16/2021	

Page 3 of 19 Print Date 12/17/2021

Quartz	>= 0.3 - < 1	14808-60-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	:	Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an



CORE™ SELF ADHERING PLASTISOL QPB-LA93 I

Version Number 1.0 Revision Date 12/16/2021 Page 4 of 19 Print Date 12/17/2021

open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

:	Causes serious eye damage.
:	No known significant effects or critical hazards.
:	Causes skin irritation.
:	No known significant effects or critical hazards.
:	Adverse symptoms may include the following: pain watering redness
:	No specific data.
:	Adverse symptoms may include the following: pain or irritation redness
:	blistering may occur Adverse symptoms may include the following: stomach pains
tentio	on and special treatment needed, if necessary
:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
:	No specific treatment.
:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing
	: : : : tentio

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: In case of fire, use water spray (fog), foam, dry chemical or CO₂.



CORE™ SELF ADHERING PLASTISOL QPB-LA93 I

Version Number 1.0 Revision Date 12/16/2021 Page 5 of 19 Print Date 12/17/2021

Unsuitable extinguishing media	:	None known.
Specific hazards arising from the chemical	:	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	:	May emit Hydrogen Chloride (HCl). Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for contain	nent a	nd cleaning up
Small spill Large spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water- insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses,
		5/19



CORE[™] SELF ADHERING PLASTISOL QPB-LA93 I

Version Number 1.0 Revision Date 12/16/2021 Page 6 of 19 Print Date 12/17/2021

basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a well-ventilated place. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits



CORE™ SELF ADHERING PLASTISOL QPB-LA93 I

Version Number 1.0 Revision Date 12/16/2021 Page 7 of 19 Print Date 12/17/2021

Ingredient name	Exposure limits		
Calcium oxide	ACGIH TLV (1994-09-01) TWA 2 mg/m3 NIOSH REL (1994-06-01) TWA 2 mg/m3 OSHA PEL 1989 (1989-03-01) TWA 5 mg/m3 OSHA PEL (1993-06-30) TWA 5 mg/m3		
Naphtha, petroleum, hydrotreated heavy	None.		
Resorcinol	ACGIH TLV (1996-05-18) TWA 45 mg/m3 10 ppm STEL 90 mg/m3 20 ppm NIOSH REL (1994-06-01) TWA 45 mg/m3 10 ppm STEL 90 mg/m3 20 ppm OSHA PEL 1989 (1989-03-01) TWA 45 mg/m3 10 ppm STEL 90 mg/m3 20 ppm		
Quartz	OSHA PEL 1989 (1989-03-01) TWA 0.1 mg/m3 (Calculated as Quartz) Form: Respirable dust OSHA PEL Z3 (1997-09-03) TWA 250 MPPCF / (%SiO2+5) Form: Respirable TWA 10 MG /M3 / (%SiO2+2) Form: Respirable OSHA PEL Z3 (1997-09-03) TWA 30 MG /M3 / (%SiO2+2) Form: Total dust NIOSH REL (1994-06-01) TWA 0.05 mg/m3 Form: Respirable dust ACGIH TLV (2005-12-09) TWA 0.025 mg/m3 Form: Respirable fraction OSHA PEL (2016-06-23) TWA 0.05 mg/m3 Form: Respirable dust		

Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers,



CORE™ SELF ADHERING PLASTISOL QPB-LA93 I

Version Number 1.0 Revision Date 12/16/2021 Page 8 of 19 Print Date 12/17/2021

		filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

ÄVIENT

CORE™ SELF ADHERING PLASTISOL QPB-LA93 I

Version Number 1.0 Revision Date 12/16/2021 Page 9 of 19 Print Date 12/17/2021

Physical state	:	liquid [liquid]
Color	:	NO PIGMENT
Odor	:	Not available.
Odor threshold	:	Not available.
pH	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n-	:	Not available.
octanol/water		
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	Dynamic: Not available.
		Kinematic: Not available.
Aerosol product		
Heat of combustion	:	Not available.
Ignition distance	:	Not available.
Enclosed space ignition - Time	:	Not available.
equivalent		
Enclosed space ignition -	:	Not available.
Deflagration density		
Flame height	:	Not available.
Flame duration	:	Not available.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.	
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).	
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will	
9/19			



CORE™ SELF ADHERING PLASTISOL QPB-LA93 I

Version Number 1.0 Revision Date 12/16/2021 Page 10 of 19 Print Date 12/17/2021

		not occur.
Conditions to avoid	:	Keep away from extreme heat and oxidizing agents.
Incompatible materials	:	Avoid contact with acetal homopolymers and acetyl homopolymers during processing.
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure				
Naphtha (petroleum), hydrotrea	Naphtha (petroleum), hydrotreated heavy A complex combination of hydrocarbons obtained by treating a petroleum							
fraction with hydrogen in the pr	esence of a catalyst.	It consists of hydroca	arbons having carbon i	numbers				
predominantly in the range of C	6 through C13 and l	poiling in the range of	approximately 65.deg	ree.C to				
230.degree.C (149.degree.F to 4	146.degree.F).							
	LD50 Oral Rat 6,000 mg/kg -							
	LC50 Inhalation	Rat	8.5 Mg/l	4 h				
Vapor								
1,3-Benzenediol								
	LD50 Oral	Rat	202 mg/kg	-				
	LD50 Dermal	Rabbit	3,360 mg/kg	-				

Conclusion/Summary

: Mixture.Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
1,3-Benzenediol	Skin - Moderate irritant	Rabbit	-	24 hrs	-
	Skin - Severe irritant	Rabbit	-		-
	Eyes - Severe irritant	Rabbit	-		-
	Eyes - Severe irritant	Rabbit	-		-

Conclusion/Summary Skin	:	Mixture.Not fully tested.
Eyes	:	Mixture.Not fully tested.
Respiratory	:	Mixture.Not fully tested.
<u>Sensitization</u>		
<u>Sensitization</u> Conclusion/Summary		
	:	Mixture.Not fully tested.

10/19



CORE™ SELF ADHERING PLASTISOL QPB-LA93 I

Version Number 1.0	Page 11 of 19
Revision Date 12/16/2021	Print Date 12/17/2021

Mutagenicity

Carcinogenicity

Conclusion/Summary	:	Mixture.Not fully tested.
--------------------	---	---------------------------

Classification

Product/ingredient name	OSHA	IARC	NTP
1,3-Benzenediol	-	3	-
Quartz	-	1	Known to be a human carcinogen.

Reproductive toxicity

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Calcium oxide	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Quartz	Category 1	-	-

Aspiration hazard

Name	Result
Naphtha (petroleum), hydrotreated heavy A complex	ASPIRATION HAZARD - Category 1
combination of hydrocarbons obtained by treating a	
petroleum fraction with hydrogen in the presence of a	
catalyst. It consists of hydrocarbons having carbon	
numbers predominantly in the range of C6 through C13	
and boiling in the range of approximately 65.degree.C to	
230.degree.C (149.degree.F to 446.degree.F).	

Information on the likely routes of : Not available.



CORE™ SELF ADHERING PLASTISOL QPB-LA93 I

Version Number 1.0 Revision Date 12/16/2021 Page 12 of 19 Print Date 12/17/2021

exposure

	<u>Potential</u>	acute	health	<u>effects</u>
--	------------------	-------	--------	----------------

Eye contact Inhalation Skin contact Ingestion	:	Causes serious eye damage. No known significant effects or critical hazards. Causes skin irritation. No known significant effects or critical hazards.
Symptoms related to the physical, ch		-
Symptoms related to the physical, ch	lenn	cal and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following: pain, watering, redness
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: pain or irritation, redness, blistering may occur
Ingestion	:	Adverse symptoms may include the following: stomach pains
Delayed and immediate effects and a	lso o	chronic effects from short and long term exposure
Short term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Long term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	No known significant effects or critical hazards.
Developmental effects Fertility effects	:	No known significant effects or critical hazards. No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral	Dermal	Inhalation	Inhalation	Inhalation



CORE™ SELF ADHERING PLASTISOL QPB-LA93 I

Version Number 1.0 Revision Date 12/16/2021 Page 13 of 19 Print Date 12/17/2021

			(gases)	(vapors)	(dusts and mists)
CORE™ SELF ADHERING PLASTISOL QPB-LA93 I	20,139.6 mg/kg	334,995.7 mg/kg	N/A	598 Mg/l	N/A
Naphtha (petroleum), hydrotreated heavy A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65.degree.C to 230.degree.C (149.degree.F to 446.degree.F).	6,000 mg/kg	N/A	N/A	8.5 Mg/l	N/A
1,3-Benzenediol	202 mg/kg	3,360 mg/kg	N/A	N/A	N/A

Other information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Section 12. Ecological information

:

Toxicity

Product/ingredient name	Result	Species	Exposure
Calcium oxide			
	Chronic NOEC 100 Mg/l Fresh	Fish - Oreochromis niloticus	46 d
	water		
1,3-Benzenediol			
	Acute LC50 40 Mg/l Fresh water	Fish - Pimephales promelas	96 h
	Acute LC50 78 Mg/l Marine	Crustaceans - Palaemonetes	48 h
	water	pugio	
	Acute LC50 > 100 Mg/l Fresh	Daphnia - Daphnia pulicaria	48 h
	water		

Conclusion/Summary

Not available.

:



CORE™ SELF ADHERING PLASTISOL QPB-LA93 I

Version Number 1.0 Revision Date 12/16/2021 Page 14 of 19 Print Date 12/17/2021

Persistence and degradability

Conclusion/Summary

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Calcium oxide	-	2.34	low
Naphtha (petroleum), hydrotreated	-	10.00 - 2,500.00	high
heavy A complex combination of			
hydrocarbons obtained by treating a			
petroleum fraction with hydrogen in			
the presence of a catalyst. It consists			
of hydrocarbons having carbon			
numbers predominantly in the range			
of C6 through C13 and boiling in the			
range of approximately 65.degree.C to			
230.degree.C (149.degree.F to			
446.degree.F).			
1,3-Benzenediol	0.8	3.16	low

Mobility in soil

Soil/water partition coefficient (KOC)	:	Not available.	
(KUC)			

Other adverse effects : No known significant effects or critical hazards.

:

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty



CORE™ SELF ADHERING PLASTISOL QPB-LA93 I

Version Number 1.0 Revision Date 12/16/2021 Page 15 of 19 Print Date 12/17/2021

containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Listed

Ingredient	CAS #	Status	Reference number
Resorcinol	108-46-3	Listed	

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	:	Not regulated for transportation.
International Air ICAO/IATA	:	Consult mode specific transport rules
International Water IMO/IMDG	:	Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations	:	United States - TSCA 12(b) - Chemical export notification: None
		of the components are listed.
		United States - TSCA 4(a) - Final Test Rules: Not listed
		United States - TSCA 4(a) - ITC Priority list: Not listed
		United States - TSCA 4(a) - Proposed test rules: Not listed
		United States - TSCA 4(f) - Priority risk review: Not listed
		United States - TSCA 5(a)2 - Final significant new use rules: Not
		listed
		United States - TSCA 5(a)2 - Proposed significant new use rules:
		Not listed
		United States - TSCA 5(e) - Substances consent order: Not listed
		United States - TSCA 6 - Final risk management: Not listed
		United States - TSCA 6 - Proposed risk management: Not listed
		United States - TSCA 8(a) - Chemical risk rules: Not listed
		United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed
		United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not
		determined
		United States - TSCA 8(a) - Preliminary assessment report
		(PAIR): Not listed
		United States - TSCA 8(c) - Significant adverse reaction (SAR):
		15/19



CORE™ SELF ADHERING PLASTISOL QPB-LA93 I

Version Number	er 1.0
Revision Date	12/16/2021

Page 16 of 19 Print Date 12/17/2021

Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Phenol United States - EPA Clean water act (CWA) section 311 -Hazardous substances: Listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed Clean Air Act Section 112(b) Listed • Hazardous Air Pollutants (HAPs)

Hazai ubus Ali Tohutants (HATS)		
Clean Air Act Section 602 Class I	:	Not listed
Substances		
Clean Air Act Section 602 Class II	:	Not listed
Substances		
DEA List I Chemicals (Precursor	:	Not listed
Chemicals)		
DEA List II Chemicals (Essential	:	Not listed
Chemicals)		

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification

: SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1 CARCINOGENICITY - Category 1A

Composition/information on ingredients

Name	%	Classification
Calcium oxide	>= 10 - < 20	SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Respiratory tract irritation - Category 3
Naphtha (petroleum), hydrotreated heavy A complex combination of hydrocarbons obtained by	>= 1 - <= 3	FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY - inhalation - Category 3 ASPIRATION HAZARD - Category 1



CORE™ SELF ADHERING PLASTISOL QPB-LA93 I

Version Number 1.0 Revision Date 12/16/2021 Page 17 of 19 Print Date 12/17/2021

treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65.degree.C to 230.degree.C (149.degree.F to 446.degree.F).		
1,3-Benzenediol	>= 1 - <= 3	ACUTE TOXICITY - oral - Category 3 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A
Quartz	>= 0.3 - < 1	CARCINOGENICITY - inhalation - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Not applicable.

State regulations		
Massachusetts	:	None of the components are listed.
New York	:	The following components are listed: Resorcinol
New Jersey Pennsylvania	:	The following components are listed: Calcium carbonate Ethene, chloro-, homopolymer Calcium oxide Resorcinol Quartz The following components are listed: Calcium carbonate
		Calcium carbonate Calcium oxide Resorcinol
		Quartz
<u>California Prop. 65</u>		



CORE™ SELF ADHERING PLASTISOL QPB-LA93 I

Version Number 1.0 Revision Date 12/16/2021 Page 18 of 19 Print Date 12/17/2021

WARNING: This product can expose you to Quartz, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Quartz	-	-

United States inventory (TSCA 8b)	:	All components are active or exempted.
Canada inventory	:	At least one component is not listed in DSL but all such components are listed in NDSL.
International regulations		
Inventory list		
Australia	:	Not determined.
Canada	:	At least one component is not listed in DSL but all such components are listed in NDSL.
China	:	All components are listed or exempted.
Europe inventory	:	All components are listed or exempted.
Japan	:	Not determined.
New Zealand	:	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	All components are listed or exempted.
Turkey	:	Not determined.
United States	:	All components are active or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on



CORE™ SELF ADHERING PLASTISOL QPB-LA93 I

Version Number 1.0 Revision Date 12/16/2021 Page 19 of 19 Print Date 12/17/2021

HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

Histor		
Date of printing	:	12/17/2021
Date of issue/Date of revision	:	12/16/2021
Date of previous issue	:	00/00/0000
Version	:	1.0
Key to abbreviations	:	ATE = Acute Toxicity Estimate
•		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From
		Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)
		UN = United Nations
References	:	Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.