

CORE<sup>™</sup> AM100 PURPLE HH-70 (WABASH)

Version Number 1.1 Revision Date 03/05/2024 Page 1 of 18 Print Date 03/06/2024

# SAFETY DATA SHEET

### CORETM AM100 PURPLE HH-70 (WABASH)

Section 1. Identification	n	
GHS product identifier	:	CORE™ AM100 PURPLE HH-70 (WABASH)
Chemical name	:	Mixture
CAS number	:	Mixture
Other means of identification	:	FO20049893
Product type	:	liquid
••		•
Relevant identified uses of the subs	tance	or mixture and uses advised against
Product use	:	Industrial applications. Plastics.
Supplier's details	:	AVIENT CORPORATION
		33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (844) 4AVIENT
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or
(with hours of operation)		accident).

# Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

#### **GHS label elements**



# CORE™ AM100 PURPLE HH-70 (WABASH)

Version Number 1.1 Revision Date 03/05/2024

#### Page 2 of 18 Print Date 03/06/2024

Hazard pictograms		
Signal word Hazard statements	<ul> <li>Danger</li> <li>Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation.</li> </ul>	
Precautionary statements		
Prevention Response	<ul> <li>Not applicable.</li> <li>Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Keep container tightly closed. Wash thoroughly after handling.</li> <li>IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye</li> </ul>	
Storage Disposal Supplemental label elements Hazards not otherwise classified	<ul> <li>irritation persists: Get medical advice or attention.</li> <li>Store in a well-ventilated place. Keep cool.</li> <li>Dispose of contents and container in accordance with all local, regional, national and international regulations.</li> <li>None known.</li> <li>None known. Not available.</li> </ul>	

# Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	FO20049893

#### CAS number/other identifiers

Ingredient name	%	CAS number
Methyl ethyl ketone	>= 50 - <= 54	78-93-3



# CORE<sup>™</sup> AM100 PURPLE HH-70 (WABASH)

Version Number 1.1 Revision Date 03/05/2024 Page 3 of 18 Print Date 03/06/2024

Titanium dioxide	>= 1 - <= 3	13463-67-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

Potential acute health effects	
Eye contact Inhalation	serious eye irritation. wn significant effects or critical hazards.



# CORE™ AM100 PURPLE HH-70 (WABASH)

Version Number 1.1 Revision Date 03/05/2024 Page 4 of 18 Print Date 03/06/2024

Skin contact Ingestion	<ul><li>Causes skin irritation.</li><li>No known significant effects or critical hazards.</li></ul>
Over-exposure signs/symptoms	
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Indication of immediate medica	al attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

# **Section 5. Fire-fighting measures**

#### **Extinguishing media**

Suitable extinguishing media Unsuitable extinguishing media	:	Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam. Do not use water jet.
Specific hazards arising from the chemical	:	Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Hazardous thermal decomposition products	:	May emit Hydrogen Chloride (HCl). Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any
		4/4.0



# CORE™ AM100 PURPLE HH-70 (WABASH)

Version Number 1.1 Revision Date 03/05/2024 Page 5 of 18 Print Date 03/06/2024

		personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-
		exposed containers cool.
Special protective equipment for	:	Fire-fighters should wear appropriate protective equipment and self-
fire-fighters		contained breathing apparatus (SCBA) with a full face-piece operated
		in positive pressure mode.

# Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel For emergency responders	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note
For emergency responders	•	of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containme	ent a	nd cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Use spark- proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Use spark- proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non- combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# CORE<sup>™</sup> AM100 PURPLE HH-70 (WABASH)

Version Number 1.1 Revision Date 03/05/2024 Page 6 of 18 Print Date 03/06/2024

# **Section 7. Handling and storage**

#### Precautions for safe handling

Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits			
Methyl ethyl ketone	OSHA PEL 1989 (1989-03-01) TWA 590 mg/m3 200 ppm STEL 885 mg/m3 300 ppm OSHA PEL (1993-06-30) TWA 590 mg/m3 200 ppm			
6/18				



# CORE<sup>™</sup> AM100 PURPLE HH-70 (WABASH)

Version Number 1.1 Revision Date 03/05/2024 Page 7 of 18 Print Date 03/06/2024

	NIOSH REL (1994-06-01) TWA 590 mg/m3 200 ppm STEL 885 mg/m3 300 ppm ACGIH TLV (1994-09-01) TWA 590 mg/m3 200 ppm STEL 885 mg/m3 300 ppm
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (2022-01-06) TWA 0.2 mg/m3 Form: respirable fraction, nanoscale particles TWA 2.5 mg/m3 Form: respirable fraction, finescale particles

Appropriate engineering controls Environmental exposure controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures		
Hygiene measures Eye/face protection	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved
		7/18



# CORE™ AM100 PURPLE HH-70 (WABASH)

Version Number 1.1 Revision Date 03/05/2024 Page 8 of 18 Print Date 03/06/2024

	standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product., When there is a risk of ignition from static electricity, wear anti-static protective clothing., For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

#### Appearance

Physical state Color Odor Odor threshold pH Melting point Boiling point Flash point	: : : : : : : : : : : : : : : : : : : :	liquid [liquid] PURPLE Not available. Not available. Not available. Not available. Not available. 25 °F (-4 °C)
Burning time Burning rate Evaporation rate Flammability (solid, gas) Lower and upper explosive (flammable) limits Vapor pressure Vapor density Relative density Solubility		Not available. Not available. Not available. <b>Lower:</b> Not available. <b>Upper:</b> Not available. Not available. Not available. Not available. Not available. Not available.



# CORE™ AM100 PURPLE HH-70 (WABASH)

Version Number 1.1 Revision Date 03/05/2024 Page 9 of 18 Print Date 03/06/2024

Solubility in water	:	Not available.
Partition coefficient: n-	:	Not applicable.
octanol/water		
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	Dynamic: Not available.
		Kinematic: Not available.

# Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	:	Avoid contact with acetal homopolymers and acetyl homopolymers during processing. Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

<u>Acute toxicity</u>				
Product/ingredient name	Result	Species	Dose	Exposure
2-Butanone				
	LD50 Oral	Rat	2,737 mg/kg	-
	LD50 Dermal	Rabbit	6,480 mg/kg	-
Titanium oxide (TiO2)				
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h
	Dusts and mists			
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-

Conclusion/Summary

: Mixture.Not fully tested.

#### Irritation/Corrosion



# CORE™ AM100 PURPLE HH-70 (WABASH)

Version Number 1.1 Revision Date 03/05/2024 Page 10 of 18 Print Date 03/06/2024

Product/ingredient name	Result		Species	Score	Exposure	Observation
2-Butanone	Skin - Mild irritant		Rabbit	-	24 hrs	-
	Skin - Moderate irritant		Rabbit	-	24 hrs	-
	Skin - Mild	l irritant	Rabbit	-	24 hrs	-
Conclusion/Summary Skin Eyes Respiratory <u>Sensitization</u>	: : :	Mixture.Not Mixture.Not Mixture.Not	fully tested.			
Conclusion/Summary Skin Respiratory	:	Mixture.Not Mixture.Not				
<b>Mutagenicity</b>						
Conclusion/Summary	:	Mixture.Not	fully tested.			
<b>Carcinogenicity</b>						
Conclusion/Summary	:	Mixture.Not	fully tested.			
<b>Classification</b>						
Product/ingredient name	OSHA	IARC	NTE	)		
Titanium oxide (TiO2)	-	2B	-			
<b>Reproductive toxicity</b>						
Conclusion/Summary	:	Mixture.Not	fully tested.			
<b>Teratogenicity</b>						
Conclusion/Summary	:	Mixture.Not	fully tested.			
Specific target organ toxicity Not available.	(single expo	<u>osure)</u>				

#### Specific target organ toxicity (repeated exposure) Not available.

#### Aspiration hazard

Not available.



# CORE™ AM100 PURPLE HH-70 (WABASH)

Version Number 1.1 Revision Date 03/05/2024 Page 11 of 18 Print Date 03/06/2024

Information on the likely routes of exposure	:	Not available.
Potential acute health effects		
Eye contact	:	Causes serious eye irritation.
Inhalation		No known significant effects or critical hazards.
Skin contact	:	Causes skin irritation.
Ingestion	:	No known significant effects or critical hazards.
Symptoms related to the physical, ch	emic	al and toxicological characteristics
Eye contact	:	Adverse symptoms may include the following: pain or irritation, watering, redness
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation, redness
Ingestion	:	No specific data.
Delayed and immediate effects and a	lso c	hronic effects from short and long term exposure
Short term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Long term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	-	Not available.
Developmental effects	:	Not available.
Fertility effects	:	No known significant effects or critical hazards.
Numerical measures of toxicity		
Acute toxicity estimates		

Product/ingredient name	Oral	Dermal	Inhalation	Inhalation	Inhalation
		11/18			



CORE<sup>™</sup> AM100 PURPLE HH-70 (WABASH)

Version Number 1.1 Revision Date 03/05/2024 Page 12 of 18 Print Date 03/06/2024

			(gases)	(vapors)	(dusts and mists)
CORE™ AM100 PURPLE HH-70 (WABASH)	5000.4 mg/kg	N/A	N/A	N/A	N/A
2-Butanone	2737 mg/kg	6480 mg/kg	N/A	N/A	N/A
Titanium oxide (TiO2)	N/A	N/A	N/A	N/A	6.82 Mg/l

#### **Other information**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

# Section 12. Ecological information

:

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
2-Butanone			
	Acute LC50 3,220 Mg/l Fresh water	Fish - Pimephales promelas	96 h
	Acute EC50 5.091 Mg/l Fresh water	Daphnia - Daphnia magna	48 h
	Acute EC50 > 500 Mg/l Marine water	Algae - Skeletonema costatum	96 h
Titanium oxide (TiO2)			
	Acute LC50 > 1,000 Mg/l Marine water	Fish - Fundulus heteroclitus	96 h
	Acute LC50 3 Mg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 h
	Acute LC50 6.5 Mg/l Fresh water	Daphnia - Daphnia pulex	48 h

#### **Conclusion/Summary**

: Not available.

:

Persistence and degradability

Conclusion/Summary

Not available.

#### **Bioaccumulative potential**



# CORE<sup>™</sup> AM100 PURPLE HH-70 (WABASH)

Version Number 1.1 Revision Date 03/05/2024 Page 13 of 18 Print Date 03/06/2024

Product/ingredient name	LogPow	BCF	Potential
2-Butanone	0.29	-	low

#### Mobility in soil

Soil/water partition coefficient (KOC)	:	Not available.
Other adverse effects		No known significant effects or critical hazards.

# Section 13. Disposal considerations

		1 1
Disposal methods	<ul> <li>The generation of waste should be avoided or minimize possible. Disposal of this product, solutions and any by</li> </ul>	
	should at all times comply with the requirements of en-	1
	protection and waste disposal legislation and any regio	
	authority requirements. Dispose of surplus and non-rec	
	products via a licensed waste disposal contractor. Wast	
	1 1	
	disposed of untreated to the sewer unless fully complia	
	requirements of all authorities with jurisdiction. Waste	1 0 0
	should be recycled. Incineration or landfill should only	
	when recycling is not feasible. This material and its con	
	disposed of in a safe way. Care should be taken when h	U
	emptied containers that have not been cleaned or rinsed	l out. Empty
	containers or liners may retain some product residues.	Vapor from
	product residues may create a highly flammable or exp	losive
	atmosphere inside the container. Do not cut, weld or gr	ind used
	containers unless they have been cleaned thoroughly in	ternally. Avoid
	dispersal of spilled material and runoff and contact wit	n soil,
	waterways, drains and sewers.	

#### United States - RCRA Acute hazardous waste "P" List: Not listed

# United States - RCRA Toxic hazardous waste ''U'' List: ListedIngredientCAS #StatusReference numberMethyl ethyl ketone78-93-3Listed

# **Section 14. Transport information**

U.S.DOT 49CFR Ground/Air/Water Proper Shipping Name:

Resin solution



# CORE™ AM100 PURPLE HH-70 (WABASH)

Version Number	er 1.1
<b>Revision Date</b>	03/05/2024

Page 14 of 18 Print Date 03/06/2024

Technical Name:	
Hazard Class / Division	3
UN Number	UN1866
Packing Group	II
Label Required	3
International Air	
ICAO/IATA	
Proper Shipping Name:	Resin solution
Technical Name:	
Hazard Class / Division	3
UN Number	UN1866
Packing Group	II
Label Required	3
International Water	
IMO/IMDG	
Proper Shipping Name:	Resin solution
Technical Name:	
Hazard Class / Division	3
UN Number	UN1866
Packing Group	II
Label Required	3

# Section 15. Regulatory information

U.S. Federal regulations	: United States - TSCA 12(b) - Chemical export notification: None of the components are listed.
	United States - TSCA 4(a) - Final Test Rules: Not listed
	United States - TSCA 4(a) - ITC Priority list: Not listed
	United States - TSCA 4(a) - Proposed test rules: Not listed
	United States - TSCA 4(f) - Priority risk review: Not listed
	United States - TSCA 5(a)2 - Final significant new use rules: Not
	listed
	United States - TSCA 5(a)2 - Proposed significant new use rules:
	Not listed
	United States - TSCA 5(e) - Substances consent order: Not listed
	United States - TSCA 6 - Final risk management: Not listed
	United States - TSCA 6 - Proposed risk management: Not listed
	United States - TSCA 8(a) - Chemical risk rules: Not listed
	United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed
	United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not
	determined
	United States - TSCA 8(a) - Preliminary assessment report
	(PAIR): Listed Quinacridone (C.I. Pigment Violet 19)



# CORE™ AM100 PURPLE HH-70 (WABASH)

Version Number	er 1.1
<b>Revision Date</b>	03/05/2024

Page 15 of 18 Print Date 03/06/2024

		United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Listed Phthalocyanine Blue
		United States - EPA Clean water act (CWA) section 311 - Hazardous substances: Listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed United States - Department of commerce - Precursor chemical: Not listed
Clean Air Act Section 112(b)	:	Not listed
Hazardous Air Pollutants (HAPs)		
Clean Air Act Section 602 Class I Substances	:	Not listed
Clean Air Act Section 602 Class II		Not listed
Substances	•	Tot instea
DEA List I Chemicals (Precursor Chemicals)	:	Not listed
DEA List II Chemicals (Essential	:	Listed

#### US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	RQ for component
Methyl ethyl ketone	78-93-3	5,000 lb(s)
		2,270 kg
		2,270 kg
		5,000 lb(s)

#### SARA 311/312

**Chemicals**)

Classification

#### : FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

#### Composition/information on ingredients

Name	%	Classification		
2-Butanone	>= 50 - <= 54	FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2		
15/10				

# **AVIENT**

# CORE™ AM100 PURPLE HH-70 (WABASH)

Version Number 1.1 Revision Date 03/05/2024

#### Page 16 of 18 Print Date 03/06/2024

		EYE IRRITATION - Category 2A
Titanium oxide (TiO2)	>= 1 - <= 3	CARCINOGENICITY - Category 2

Not applicable.

State regulations		
Massachusetts	:	The following components are listed: Methyl ethyl ketone
		Silica gel
		Titanium dioxide
New York	:	The following components are listed:
		Methyl ethyl ketone
New Jersey	:	The following components are listed:
		Methyl ethyl ketone
		Titanium dioxide
		Methane, 1,1'-sulfinylbis-
Pennsylvania	:	The following components are listed:
		Methyl ethyl ketone
		<b>6'1'</b>
		Silica gel
		Titanium dioxide

#### California Prop. 65

**WARNING:** This product can expose you to Titanium dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Titanium dioxide	-	-

United States inventory (TSCA 8b)	:	All components are active or exempted.	
Canada inventory	:	All components are listed or exempted.	
International regulations Inventory list			
Australia	:	Not determined.	
Canada	:	All components are listed or exempted.	
China	:	All components are listed or exempted.	
<b>Eurasian Economic Union</b>	:	Russian Federation inventory: Not determined.	
		16/18	



# CORE™ AM100 PURPLE HH-70 (WABASH)

Version Number 1.1 Revision Date 03/05/2024 Page 17 of 18 Print Date 03/06/2024

Japan	:	Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined.
New Zealand	:	All components are listed or exempted.
Philippines	:	Not determined.
Republic of Korea	:	Not determined.
Taiwan	:	Not determined.
Thailand	:	Not determined.
Turkey	:	Not determined.
United States	:	All components are active or exempted.
Viet Nam	:	Not determined.

# Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

<u>Illstol y</u>		
Date of printing	:	03/06/2024
Date of issue/Date of revision	:	03/05/2024
Date of previous issue	:	03/04/2024
Version	:	1.1
Key to abbreviations	:	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
References	:	UN = United Nations Not available.
Notice to reader		



# CORE<sup>™</sup> AM100 PURPLE HH-70 (WABASH)

Version Number 1.1 Revision Date 03/05/2024 Page 18 of 18 Print Date 03/06/2024

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.